


STOREY DRILLING SERVICES

P.O. Box 98 • MIDLAND, OREGON 97634
 (541) 884-3990 • (800) 245-8122
 Fax #: (530) 528-2562

22560 ADOBE ROAD • RED BLUFF, CALIFORNIA 96080
 CONTRACTOR'S LICENSES:
 OR #601 • CA #583153 • NV #38199

Mr. Dan Chin
 17817 Cheyne Road
 Klamath Falls, Oregon 97603



RECEIVED

NOV 05 2001

WATER RESOURCES DEPT.
 SALEM, OREGON

START: September 17, 2001
 FINISH: October 12, 2001

WELL LOCATION: Corner of Malone Road & Hwy 39; ¼ mile due east of Merrill, Oregon
 SW¼ NE¼ S7 T41S R11E

LOG

0 - 12	Brown sand with streaks yellow clay
12 - 22	Yellow clay
22 - 60	Green clay
60 - 734	Gray clay
734 - 749	Black lava
749 - 752	Black basalt
752 - 760	Hard gray basalt
760 - 774	Black basalt
774 - 830	Hard gray basalt
830 - 831	Brown basalt
831 - 852	Broken black basalt
852 - 853	Hard gray basalt
853 - 860	Black basalt
860 - 863	Brown basalt
863 - 872	Black basalt
872 - 882	Hard gray basalt
882 - 940	Broken black basalt
940 - 980	Black basalt
980 - 990	Hard gray basalt
990 - 1004	Broken black basalt
1004 - 1012	Black basalt
1012 - 1049	Hard gray basalt
1049 - 1072	Black basalt
1072 - 1091	Hard gray basalt
1091 - 1109	Black basalt
1109 - 1140	Hard gray basalt
1140 - 1168	Brown lava
1168 - 1186	Hard broken gray basalt

55 feet 2 inches of 16 inch O.D. steel casing set & cemented at 54 feet.
 15 inch diameter hole from 54 feet to 200 feet; 9 7/8 inch diameter hole from 200 to 987 feet;
 8¾ inch diameter hole from 987 feet to 1186 feet
 Static water level at 55 feet; Temperature 66° Fahrenheit
 Airlifted approximately 1000 GPM at 231 feet.
 Test pumped 2600 GPM at 103 feet.