

WELL I.D. # L _____

(1) LAND OWNER Liskey Farms Inc Well Number 3
 Name Liskey Farms Inc
 Address 4650 Lower Klamath Lake Rd
 City Klamath Falls State OR Zip 97603

(2) TYPE OF WORK
 New Well Deepening Alteration (repair/recondition) Abandonment

(3) DRILL METHOD:
 Rotary Air Rotary Mud Cable Auger
 Other _____

(4) PROPOSED USE:
 Domestic Community Industrial Irrigation
 Thermal Injection Livestock Other _____

(5) BORE HOLE CONSTRUCTION:
 Special Construction approval Yes No Depth of Completed Well _____ ft.
 Explosives used Yes No Type _____ Amount _____

HOLE			SEAL			
Diameter	From	To	Material	From	To	Sacks or pounds
20"	0	282				

How was seal placed: Method A B C D E
 Other _____

Backfill placed from _____ ft. to _____ ft. Material _____
 Gravel placed from _____ ft. to _____ ft. Size of gravel _____

(6) CASING/LINER:

	Diameter	From	To	Gauge	Steel	Plastic	Welded	Threaded
Casing:					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Liner:					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Drive Shoe used Inside Outside None
 Final location of shoe(s) _____

(7) PERFORATIONS/SCREENS:

Perforations Method _____
 Screens Type _____ Material _____

From	To	Slot size	Number	Diameter	Tele/pipe size	Casing	Liner
						<input type="checkbox"/>	<input type="checkbox"/>
						<input type="checkbox"/>	<input type="checkbox"/>
						<input type="checkbox"/>	<input type="checkbox"/>

(8) WELL TESTS: Minimum testing time is 1 hour
 Pump Baller Air Flowing Artesian
 Yield gal/min _____ Drawdown _____ Drill stems at _____ Time _____
4500 _____ _____ _____ 1 hr.

Temperature of water 199°F Depth Artesian Flow Found _____
 Was a water analysis done? Yes By whom _____
 Did any strata contain water not suitable for intended use? Too little
 Salty Muddy Odor Colored Other _____
 Depth of strata: _____

(9) LOCATION OF WELL by legal description:
 County Klamath Latitude _____ Longitude _____
 Township 40 S N or S Range 9 E (B or W. WM.)
 Section 34 ACA SW 1/4 of NE 1/4
 Tax Lot 200 Lot _____ Block _____ Subdivision _____
 Street Address of Well (or nearest address) _____
4024 Lower Klamath Lake Rd

(10) STATIC WATER LEVEL:
17 ft. below land surface. Date 15 Dec 1954
 Artesian pressure _____ lb. per square inch Date _____

(11) WATER BEARING ZONES:

Depth at which water was first found _____

From	To	Estimated Flow Rate	SWL
274	282	4500 gpm	17

(12) WELL LOG:

Ground Elevation _____

Material	From	To	SWL
Top Dirt	0	3	
Hard Pan	3	6	
Yellow Chalk	6	24	
Blue & Yellow Chalk alternate	24	184	
Clay with streaks of hard shale	184	260	
Hard Blue Shale	260	274	
Pumice gravel with lots of water	274	282	17

Date started _____ Completed 15 Dec 1954

SOURCE OF DATA/INFO
Ground Water Right Application: G-16813
(see attached sheet)

COMPILED BY: GERALD H. GRONDAI
OWRD Hydrogeologist

DATE: 20 March 2007

#3

#3 well

LISKY NOT WELL BY SHOP DEC. 15, 1924
8" well

- 0-----3 Top Dirt
- 3-----6 Hard Pan
- 6-----24 Yellow Chalk
- 24-185 Blue and Yellow chalk Alternate
- 185-260 Clay with streaks of Hard shale
- 260-274 Hard blue shale
- 274-277 1/2 Pumice Gravel with lots of water.

Temperatures at 45' Luke warm
 145' 109 Degrees
 240' 124 " "
 260' 129 " "
 270' 140 " "
 277 1/2' 170 " "

277 1/2 Feet of 8" hole at \$2.00 -----\$555.00

WELL OUT BY FEED LOT 8"

- 0-----3 Top dirt
- 3-----16 Chalk
- 16-----17 Hard rocky clay
- 17-----53 Clay with streaks of shale


Water test 50 Gallons per minute drawing the
 water down 45-35'

Temperature 170 Degrees

53' of 8" hole at \$2.00 -----\$106.00

 Total \$661.00

All to apply on Leveling job.



LISKY NOT WELL BY SHOP

Reamed from 8" hole to 20" hole.

- 0-----3 Top Dirt
- 3-----6 Hard Pan
- 6-----24 Yellow Chalk
- 24-----184 Blue and Yellow chalk Alternate
- 184-----260 Clay with streaks of Hard shale
- 260-----274 Hard blue shale
- 274-----282 Pumice gravel with lots of water

Temperature when pumping 4500 Gal. Per min.
 199 Degrees.

Static water Level 17 feet.

Pumping level at 4500 Gal. 19 feet.

282 feet of 20" hole at \$5.00 -----\$1410.00

KLAM 55747

RECEIVED

FEB 27 2007

WATER RESOURCES DEPT
SALEM, OREGON