STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210)

Kl

			Page 1 of 1
LAM 59549	WELL I.D. LABEL# L	121236	-
	START CARD#	1030256	
4/25/2016	ORIGINAL LOG#		

(1) LAND OWNER Owner Well I.D.	4		
First Name Last Name	(9) LOCATION OF WELL (legal description)		
Company PACIFICORP ENERGY	County KLAMATH Twp 39.00 S N/S Range 7.00 I		
Address 925 SOUTH GRAPE ST. BLDG. 5 City MEDFORD State OR Zip 97501	Sec <u>36</u> 1/4 of the 1/4 Tax Lot <u>300</u>)	
City MEDFORD State OR Zip 97501 (2) TYPE OF WORK New Well Deepening Conversion	Tax Map Number Lot		
(2) TYPE OF WORK X 100 December 100 Conversion	Lat ° " or 42.13542000	DMS or DD	
Alteration (complete 2a & 10) Abandonment(complete 5a) (2a) PRE-ALTERATION	Tax Map Number Lot	DMS or DD	
Dia + From To Gauge Stl Plstc Wld Thrd	Street address of well Nearest address	-	
Casing:	KENO RECREATION PARK		
Material From To Amt sacks/lbs	HWY 66		
Seal:			
(3) DRILL METHOD	(10) STATIC WATER LEVEL		
Rotary Air Rotary Mud Cable Auger Cable Mud	Date SWL(psi) +	SWL(ft)	
Reverse Rotary Other	Existing Well / Pre-Alteration Completed Well 4/24/2016	7.6	
(A) PROPOGED LIGE Demotic Unication Community	Completed Well 4/24/2016	76	
(4) PROPOSED USE Domestic Irrigation Community			
Industrial/ Commercial Livestock Dewatering	WATER BEARING ZONES Depth water was first found 115.00		
Thermal Injection X Other CAMPGROUND	SWL Date From To Est Flow SWL(psi)	+ SWL(ft)	
(5) BORE HOLE CONSTRUCTION Special Standard (Attach copy)	4/24/2016 115 191 55	76	
Depth of Completed Well 191.00 ft.	4/24/2010 113 171 33	70	
BORE HOLE SEAL sacks/			
Dia From To Material From To Amt lbs			
12 0 98 Bentonite Chips 0 98 87 S			
6 98 191 Calculated 80			
	(11) WELL LOG Ground Flowston		
Calculated	Glouild Elevation		
How was seal placed: Method A B C D E	Material From	То	
Xother POURED DRY	Topsoil with boulders 0	14	
Backfill placed from ft. to ft. Material	tan soil with clay content 14	22	
Filter pack from ft. to ft. Material Size	black lava 22 soft gray lava 27	36	
Explosives used: Yes Type Amount	hard black lava 36	42	
(5a) ABANDONMENT USING UNHYDRATED BENTONITE	softer brown lava 42	44	
Proposed Amount Actual Amount	hard gray lava 44	84	
	gray sandy clay 84	88	
(6) CASING/LINER Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	hard gray lava 88	110	
	soft broken red cinder 110	138	
	broken brown lava with tan claystone 138	152	
	hard broken gray lava 152	158	
	soft broken red cinder 158	162	
	broken brown lava 162	191	
Shoe Inside Other Location of shoe(s) 98			
(7) PERFORATIONS/SCREENS			
Perforations Method		lI	
Screens Type factory Material pvc	Date Started 4/19/2016 Completed 4/24/2016		
Perf/ Casing/ Screen Scrn/slot Slot # of Tele/ Screen Liner Dia From To width length slots pipe size	(unbonded) Water Well Constructor Certification		
Screen Liner 4 171 191 .032	I certify that the work I performed on the construction, deepening	g, alteration, or	
	abandonment of this well is in compliance with Oregon wat		
	construction standards. Materials used and information reported a	bove are true to	
	the best of my knowledge and belief.		
	License Number 1940 Date 4/25/2016		
(8) WELL TESTS: Minimum testing time is 1 hour			
Pump Bailer (a) Air Flowing Artesian	Signed BENJAMIN FRY (E-filed)		
	(bonded) Water Well Constructor Certification		
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr) 55 180 1	I accept responsibility for the construction, deepening, alteration, or abandonment work performed on this well during the construction dates reported above. All work		
33			
	performed during this time is in compliance with Oregon water supply well		
Temperature 54 °F Lab analysis Yes By	construction standards. This report is true to the best of my knowledge.		
		-	
Water quality concerns? Yes (describe below) TDS amount From To Description Amount Units	License Number 1355 Date 4/25/2016		
	Signed ARTHUR L FRY (E-filed)		
	Contact Info (optional)		
	TO LOCAL STORY		