STATE OF OREGON

WATER SUPPLY WELL REPORT

(as required by ORS 537.765 & OAR 690-205-0210)

9/5/2018

WELL I.D. LABEL# L 130952 START CARD# 1039919 ORIGINAL LOG#

(1) LAND OWNER Owner Well I.D.		
First Name Y CAMP Last Name LOW ECHO Last Name LOW ECHO	(9) LOCATION OF WELL (legal description)	
Company ASHLAND FAMILY YMCA	County KLAMATH Twp 37.00 S N/S Range 5.00 E E/W WM	
Address 540 YMCA WAY	Sec 15 NW 1/4 of the SE 1/4 Tax Lot LOT5	
City ASHLAND State OR Zip 97520 (2) TYPE OF WORK New Well Deepening Conversion	Tax Map Number Lot	
(2) TYPE OF WORK New Well Decepening Conversion	Tax Map Number Lot Lat " or	DMS or DD
Alteration (complete 2a & 10) Abandonment(complete 5a) (2a) PRE-ALTERATION	Long	DMS or DD
Dia + From To Gauge Stl Plstc Wld Thrd	Street address of well Nearest address	
Casing:	Y CAMP LOW ECHO LAKE OF THE WOODS	
Material From To Amt sacks/lbs		
Seal:		
(3) DRILL METHOD	(10) STATIC WATER LEVEL	
Rotary Air Rotary Mud Cable Auger Cable Mud	Date SWL(psi) + SWL(ft) Existing Well / Pre-Alteration	
Reverse Rotary Other	Completed Well 8/17/2018 303	
(4) PROPOSED USE Domestic Irrigation X Community	Flowing Artesian? Dry Hole?	
	WATER BEARING ZONES Depth water was first found 368.00	
Thermal Injection Other	SWL Date From To Est Flow SWL(psi) + SWL(ft)	
		SWL(II)
(5) BORE HOLE CONSTRUCTION Special Standard (Attach copy)	8/17/2018 368 381 30	303
Depth of Completed Well 400.00 ft. BORE HOLE SEAL sacks/		
BORE HOLE SEAL sacks/ Dia From To Material From To Amt 1bs		
12 0 40 Bentonite Chips 0 40 118 S		-
8 40 320 Calculated 22		
6 320 378	(II) WELL LOC	
	(11) WELL LOG Ground Elevation	
How was seal placed: Method A B C D E	Material From	То
X Other DRY POURED	BROWN CLAY BOULDERS GRAVEL 0	34
Backfill placed from ft. to ft. Material	BRN VOLCANIC BASALT MED/HARD 34	97
Filter pack from ft. to ft. MaterialSize	GREY/RED VOLCANIC BASALT MED/HARD 97 GREY RED CINDERS 158	158
Explosives used: Yes Type Amount	GREY RED VOLCANIC BASALT HARD 161	276
(5a) ABANDONMENT USING UNHYDRATED BENTONITE	GREY VOLCANIC BASALT HARD 276	310
Proposed Amount Actual Amount	VOID 310	314
(6) CASING/LINER	GREY VOLCANIC BASALT HARD 314	392
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	GREY RED VOLCANIC MED HARD 392	397
	GREY VOLCANIC BASALT HARD 397	400
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$		
Shoe Inside Outside Other Location of shoe(s) 378		
Temp casing Yes Dia From + Te		
(7) PERFORATIONS/SCREENS		+
Perforations Method TORCH		
Screens Type Material Perf/ Casing/ Screen Scrn/slot Slot # of Tele/	Date Started 8/8/2018 Completed 8/15/201	8
Perf/ Casing/ Screen Scrn/slot Slot # of Tele/ Screen Liner Dia From To width length slots pipe size	(unbonded) Water Well Constructor Certification	
Perf Liner 6 354 378 188 6 78	I certify that the work I performed on the construction, deepening, alteration, or	
	abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to	
	the best of my knowledge and belief.	
	License Number 1945 Date 8/24/2018	
(8) WELL TESTS: Minimum testing time is 1 hour	Signed JUSTIN SPLIETHOF (E-filed)	
Pump Bailer • Air Flowing Artesian	JOSTIN SPEIETHOF (E-tiled)	
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	(bonded) Water Well Constructor Certification	
30 378 2	I accept responsibility for the construction, deepening, alteration, or abandonment	
	work performed on this well during the construction dates reported above. All work	
Toward at 64 OF Laborator V. D	performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.	
Temperature 54 °F Lab analysis Yes By		
Water quality concerns? Yes (describe below) TDS amount 378 pom From To Description Amount Units	License Number 1835 Date 9/5/2018	
	Signed KEVIN GILL (E-filed)	
	Contact Info (optional) CLOUSER DRILLING INC.	