## STATE OF OREGON

KLAM 60310

WELL I.D. LABEL# L 131968

WATER SUPPLY WELL REPORT			START CA	RD#	1042094	
(as required by ORS 537.765 & OAR 690-205-0210)	3/14	/2019	ORIGINAL LO	OG#		
1) LAND OWNER Owner Well I.D.				<u></u>	II.	
First Name EDWIN J. Last Name STASTNY	JR.	1 (9) 1 (1)	ATION OF WELL (I	ah lena	scription)	
Company				_	-	E EMM
Address 32121 HWY 50			AMATH Twp 41.00 S			
City MALIN State OR Zip S	97632		SE1/4 of theNE			
City MALIN State OR Zip 2  2) TYPE OF WORK New Well Deepening	Conversion	Tax Map Nu	nmber ' " or		Lot	DMG DD
Alteration (complete 2a & 10) Abai	ndonment(complete 5a)	Lat	or "or			
2a) PRE-ALTERATION				_		DMS or DD
Dia + From To Gauge Stl Plstc	Wld Thrd			( Near	est address	
Casing:		23333 EVA				
Material From To Amt sacks/ll	os —	MALIN, OI	R. 97632			
Seal:		(10) CTA		r		
B) DRILL METHOD		(10) S1A	TIC WATER LEVE	L Date	CMI (:)	L CMI (ft)
Rotary Air Rotary Mud Cable Auger	Cable Mud	Existing	g Well / Pre-Alteration	Date	SWL(psi)	F SWL(ft)
Reverse Rotary Other			eted Well		+	97.5
4) PROPOSED USE Domestic X Irrigation	Community	- T	Flowing Artesiar	?	Dry Hole?	] 77.5
Industrial/ Commercial Livestock Dewatering	Community	WATER DE	_	ш	_	]
					er was first found	
ThermalInjectionOther		SWL Date	e From To	Est F	Flow SWL(psi)	+ SWL(ft)
5) BORE HOLE CONSTRUCTION Special Sta	andard (Attach copy)					
Depth of Completed Well ft.						
BORE HOLE SEAL	sacks/	,				
Dia From To Material From	To Amt lbs	_				
20 0 93		<b>∐</b>				
10 ,0 ,0	alculated	╣ └───				
14 359 527	-11-41	1/(11) WEL	LLOG a in			
10 127 200	alculated	(11) \\	Ground L	levation		
How was seal placed: Method A B C	∐D ∐E	I	Material		From	To
Other						
Backfill placed from ft. to ft. Material		1				+ -
Filter pack from ft. to ft. Material						
Explosives used: Yes Type Amount						
5a) ABANDONMENT USING UNHYDRATED B	ENTONITE					
Proposed Amount Actual Amount						
•						
6) CASING/LINER Casing Liner Dia + From To Gauge	Stl Plstc Wld Thrd					
Casing Emer 1 110m 10 Gauge						
	KAH H					
	$\mathbb{R}$					
	$X \times X + H$					
	$X \times X + H$					
Shoe Inside Outside Other Location o	f shoe(s)					_
) PERFORATIONS/SCREENS						
Perforations Method				_		
Screens Type Materia Perf/ Casing/ Screen Scrn/slot S		Date Start	ted3/5/2019	Comp	leted <u>3/11/2019</u>	)
Perf/ Casing/ Screen Scrn/slot S. Screen Liner Dia From To width len		(unbonded)	) Water Well Constructor	Certifica	ation	
Screen Emer Bia 140m 10 width len	gui siots pipe size	1 '	at the work I performed or			ning, alteration, o
		abandonme	nt of this well is in cor	npliance	with Oregon v	vater supply wel
		construction	n standards. Materials used	and info	rmation reported	l above are true to
		the best of r	ny knowledge and belief.			
		License Nu	mber	Date	e	
WELL TESTS: Minimum testing time is 1 hour				_		
	Elevine Antonion	Signed				
Pump Bailer • Air	) Flowing Artesian		7.4. W. H. G	4.6.		
Yield gal/min Drawdown Drill stem/Pump depth	Duration (hr)	` ′	ater Well Constructor Ce			
1200 520	2		ponsibility for the construc			
			med on this well during the			
			during this time is in con standards. This report is tr			
Temperature 65 °F Lab analysis Yes By		-	_		-	reage and benef.
Water quality concerns? Yes (describe below) TDS am	ount 284 ppm	License Nur	mber 1355	Date	3/14/2019	
From To Description	Amount Units	Signad .				
	+ + +		RTHUR FRY (E-filed)			
	+ +	Contact Info	o (optional)			

KLAM 60310

3/14/2019

WELL I.D. LABEL# L 1 START CARD # 1 ORIGINAL LOG #

BEL# L	131968	
ARD#	1042094	
LOG#		

	E-AL	TERA							Water Q	uality Conc	erns				
Dia	+	From	To C	auge Stl	Plstc W	ld Thrd			From	To	Descri	ption	Amo	ount	Units
				$ \Box$		↓ Н									
	┥├┼			$\longrightarrow \not \models$	+++	H									
Ma	l LLL terial		From	To	Amt sack	s/lbs									
1,10			110111	10	7 mit sack	.5/103									
									(10) CTA	TIC WAT	ED I EXTEI				
5) BOI	RE HO	OLE CO	ONSTRU	JCTION	<b>J</b>				SWL Dat		ER LEVEL		CMAT ( ')		CIVIT (C)
	RE H				SEA	AL		sacks/	SWL Dat	e From	То	Est Flow	SWL(psi)	, + 	SWL(ft)
Dia	From	To	M	aterial	Fror		Amt	lbs						$+$ $\vdash$ $\vdash$	
														1 H	
			1			Calculate	ed	+						] [	
														-∤   Ц	
		_	_			Calculate	ed	+				_		$+$ $\vdash$ $\vdash$	
			$\dashv$ $\vdash$			Calculate	ed	+				1		┨	
														1 H	
						Calculate	ed								
	FILTE	ER PACE	ζ						(11) WEI	LLOG					
Fı	om	То	Material	Size	;				(11) ***						_
										Materi	al		From	—_г	То
													+		
													1		
) CAS	ING/	LINER													
Casir	o Line	Dia	+ F	rom To	Gauge	Stl Pls	to Wld	Thrd							
Cusii	ig Eme	Dia	+ 1	10111 10	Guuge	50 115	ic wia	Tinu					+		
$\bigcirc$													1		
Q															
Q	9						$A \sqcup A$	Ш							
$\otimes$	$\rightarrow$					$\mid \hspace{-0.5em} \mid \hspace{-0.5em} \mid \hspace{-0.5em} \mid \hspace{-0.5em} \mid \hspace{-0.5em} \mid \hspace{-0.5em} \mid \hspace{-0.5em} -0.5em$	$\forall$	$\mathbb{H}$					+		
$\bowtie$	$\dashv$		<del>                                     </del>			$\mid \hspace{-0.1cm} \mid \hspace{-0.1cm} \mid \hspace{-0.1cm} \hspace{-0.1cm} \mid \hspace{-0.1cm} \mid \hspace{-0.1cm} \mid \hspace{-0.1cm} \mid \hspace{-0.1cm} \hspace{-0.1cm} \mid \hspace{-0.1cm} \hspace{-0.1cm} \mid \hspace{-0.1cm} \mid \hspace{-0.1cm} \hspace{-0.1cm} \mid \hspace{-0.1cm} \mid \hspace{-0.1cm} \hspace{-0.1cm} \mid \hspace{-0.1cm} \hspace{-0.1cm} \mid -0.1$	$\forall$	H					1		
$\sim$	$\exists$						<b>∮</b>	H							
Ŏ							<b>∄</b> □								
Ŏ														-+	
\ DED	EOD	ATTON	G/GCDE	TENIC											
) PEK	TOK.	ATION	S/SCRE	ENS											
Perf/				_	Scrn/slot	Slot	# of	Tele/					_		
Screen	Liner	Dia	From	То	width	length	slots	pipe size							
									I <del></del>						
								1					+	$ \vdash$	
					1			+					+		
													-		
									Comme	nts/Remar	KS				
									refer to we	ell KLAM/105	39. From 359' t	o 527' we op	ened from	10" to	14"
(8) WI	ELL T	ESTS:	Minimu	ım testin	ig time is	s 1 hour				se was done to		1			
Yield ;	gal/min	Drav	wdown	Drill ster	n/Pump de	pth D	uration (	(hr)							
								$\neg$							
						1		$\dashv$							
		+						$\dashv$							
								$\dashv$							
						-			1.1						