File Original and First Copy with the STATE ENGINEER, SALEM OREGON

OCT 11 1962 WATER WELL REPORT COTATE IN GINEER STATE OF OREGON COLORS

SALEM, OREGON	board 1	G 2010 Sattle 1 Sattl		
Name Warner Valley Stock		(11) WELL TESTS: Drawdown is amount we lowered below static level. Was a pump test made? Yes \(\sqrt{N}\) No. If yes, by whom	vater level vel. In t pump	erstat
Address Klamath Falls, Oregon		Yield: 1500 gal./min. with 7 ft. drawdow		
		2) 2) 2)		
(2) LOCATION OF WELL: County Klamath Owner's number, if any—		Bailer test gal./min. with ft. drawdown after		hrs.
		Artesian flow 75 g.p.m. Date 10/4/62		
N.W. 14 N.W. 14 Section] O	231 S. R. 8 E. W.M.	Temperature of water 12 Was a chemical analysis ma	., -	s 🛛 No
Bearing and distance from section or subdivis	sion corner			***************************************
		(12) WELL LOG: Diameter of well Depth drilled 160 ft. Depth of completed w	ell 104	ft.
		Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of a stratum penetrated, with at least one entry for each commendation.	1	
		MATERIAL	FROM	TO
(3) TYPE OF WORK (check): New Well Deepening □ Reconditioning □ Abandon □		peat and top soil	0	<u>4½</u>
		white pumice	$\frac{4^{\frac{1}{2}}}{}$	
If abandonment, describe material and proces	dure in Item 11.	pink pumice and sand	7	_29
PROPOSED USE (check):	(5) TYPE OF WELL:	white pumice and sand	29 42	42
Domestic Industrial Municipal	Rotary Driven	black sand and pumice		_ <u>52</u> _58
Irrigation ☐ Test Well ☐ Other ☐	Cable X Jetted Dug Bored D	course quick sand, some grave packed sand and pumice	<u> 58</u>	<u> </u>
	Dug L Borea L	loose course sand and pumice	73	82
	hreaded Welded	sandstone	82	85
18 " Diam, from	156 ft. Gage	quick sand and gravel	85	87
20 " Diam. from	28 ft. Gage 4	packed sand and pumice	87	89
Tt. Gage ft. Gage		clay and pumice	89	91
(7) PERFORATIONS: Perforated? Yes No		big gravel and sand	91	97
Type of perforator used <u>factory</u>	eriorated: A res 110	yellow clay	97	100
	7 ½in.	sandstone	100	103
SIZE of perforations 3/16 in. by perforations from	ft. to ft.	sand, gravel & pumice	103	139
perforations from		cemented gravel	139	142
perforations from		gravel and sand	142 156	156
perforations from		gray lava	150	160
perforations from	ft. 'to ft.			
` '	installed Yes No			
Manufacturer's Name				
Type	ft. to ft.			
Slot size Set from		Work started 9/19 1962 Completed 1	0/4	19 62
Stot size Set I zer		work stated 27 2 13 -, Completed		
(9) CONSTRUCTION:		(13) PUMP:		
Was well gravel packed? ☐ Yes ※ No Size of gravel:		Manufacturer's Name	***************************************	
Gravel placed from		Type:	H.P	
Was a surface seal provided? You Yes No Material used in seal— Portland C	emerr c	Well Driller's Statement:		1
Did any strata contain unusable water?		This well was drilled under my jurisdiction a	and this	report is
	of strata	true to the best of my knowledge and belief.		
Method of sealing strata off		NAME John A. Van Meter	ype or prin	
(10) WATER LEVELS:		1	-	t)
	d surface Date $10/4/62$	Address Box 204 Malin, Oregon		
Artesian pressure 2 lbs. per sq	uare inch Date $10/4/62$	Driller's well number	<i>A</i>	•••••
Log Accepted by: Valla Str	10-8 .15	[Signed] Janua (Well Driller)	E P	
[Signed] Date (Owner)	9 <u> </u>	License No. 170 Date $10/8$, .	<u>, 1962</u>