NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

Klam 675 State Well No. 3/5/8E-200

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:			
Name John M. Mosby	County Klamath Driller's well number			
Address P.O. Box 1175 Lompoc, Calif. 93436	N.W 1/4 S.W 1/4 Section 20 T. 31 S R. 8 E W.M.			
(a) HVDE OF WORK (1 1)	Bearing and distance from section or subdivisi	on corner		
(2) TYPE OF WORK (check):				
New Well Deepening Reconditioning Abandon	-			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 4 ft			
Domestic ☐ Industrial ☐ Municipal ☐	Static level 4 ft. below land s	surface. Da	ate 7/	′ 31/78
Dos 🛘 Bored 🗀 Irrigation 🖵 Test Well 🗎 Other 🖂	Artesian pressure lbs. per square inch. Date			
(5) CASING INSTALLED: Threaded □ Welded ☑ 20 ft. to 25½ ft. Gage ½"	(12) WELL LOG: Diameter of well below casing			
"Diam from 0 ft to 322 ft Gage 11"	Depth drilled 322 ft. Depth of completed well 322 ft			ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size	and structu	re of r	naterials;
(e) DEDECT AMIONS.	and show thickness and nature of each stratu with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Report	t each o	hange in
Type of perforator used Factory	MATERIAL	,	······································	
Size of perforations 1/8 in. by 3 in.		From	To	SWL
perforations from 56 ft. to 322 ft.	top soil pumice	10	26	4
perforations from ft. to ft.	sand, gravel & pumice	26	40	91
perforations from ft. to ft.	brown sand	40	46	#1
	brown sandstone	46	52	11
(7) SCREENS: Well screen installed? Yes X No	XXXXX coarse sand, pea gravel	- · · ·		****
Manufacturer's Name	& pumice	52]	154	11
Type Model No.	coarse sand & pumice		1.56	11
Diam. Slot size	pea gravel & clay	156]	160	11
Diam. Slot size Set from ft. to ft.	brown gravel & sand	160	196	**
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	brown clay & gravel	196	202	
a pump test made? Yes \(\subseteq \) No \(\text{H} \) yes, by whom? Owner	minus gravel & sand	202 3	322	**
Yield: 4000 gal./min. with 76 ft. drawdown after 4 hrs.	RECEIVED			
<i>n</i>	SEP 10 1979			·
" " " " " " " " " " " " " " " " " " "	WATER RESOURCES DEPT	 -		
r test gal./min. with ft. drawdown after hrs.	SALEM, OREGON			
Artesian flow g.p.m.				
Temperature of water 48 Depth artesian flow encountered ft.	Work started 6/17/78 19 Completed 7/31 19 7			
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7/31		1978
Well seal-Material usedcement	Drilling Machine Operator's Certification:			
Well sealed from land surface to 25	This well was constructed under my Materials used and information reported	direct s	super	vision.
Diameter of well bore to bottom of seal 24 in.	Materials used and information reported best knowledge and belief	above un	c muc	10 1119
Diameter of well bore below seal	[Signed] Joffman Lan Mells Date 9/5, 19.79.			
Number of sacks of cement used in well seal	Drilling Machine Operator's License No.			
How was cement grout placed? grout pipe	District Tion			
The second secon	Water Well Contractor's Certification:			
The state of the s	This well was drilled under my jurisdi	ction and	this re	eport is
Was a drive shoe used? ☐ YesX☐ No Plugs Size: location ft.	true to the best of my knowledge and bell Name John A. Van Meter	lef.		
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation)	(Type	or prin	.t)
Type of water? depth of strata	7 A - 1	egon		
Method of sealing strata off	1. I all In	1.		
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed]	actor)	,	
Gravel placed from ft. to ft.		9/5		19 79