NOTICE TO WATER WELL CONTRACTOR The original and first copy WATER WELL REPORT of this report are to be filed with the STATE OF QREGO State Well No. 1976 103 State Permit No. STATE ENGINEER, SALEM, OREGON 97310 (Please type or print) within 30 days from the date (Do not write above this line) of well completion. 110) Location (1) OWNER: County Lak Driller's well number 1/4 Section Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Reconditioning New Well Deepening [If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (4) PROPOSED USE (check): (3) TYPE OF WELL: Depth at which water was first found 138 Rotary Driven | ft. below land surface. Date Domestic 🔲 Industrial 🖂 Municipal 🖂 Static level Jetted | Cable Irrigation Test Well | Other Dug Bored [Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded | Welded (12) WELL LOG: Diameter of well below casing . 72 " Diam. from O ft. to OO ft. Gage Depth drilled 500 ft. Depth of completed well " Diam, from ft. to Formation: Describe color, texture, grain size and structure of materials; " Diam. from _____ ft. to ____ ft. Gage and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? | Yes | No. MATERIAL From Type of perforator used muerburden, SAND, Fiv. Size of perforations in. by DK.BRN S.L. SCFT ft. to .. perforations from 22 37 _ perforations from _____ ft. to unice White, SOF 138 DK. Green Funice + Clay perforations from 138 BIACK SAND' (7) SCREENS: Well screen installed?

Yes DK. Green PHMICE+ (AY Manufacturer's Name .. Black LAVA-SCHI-HARD 338 Fumice Green with clay 2.73 Set from Diam. Slot size BROWN CLAY, SOFT HARD BIACK LAVA BASAIT 381 395 Diam. Slot size Set from 395 444 ANDISITE BLACKER - HAKD (8) WELL TESTS: BlACK LAUA - HARD 444 454 Blue Grey Howey Conen LAVA Was a pump test made? MYes □ No If yes, by whom? Drille 454 467 HAPD-GIRY LAVA BASAIT 467 480 Yield: 1500 gal./min. with 27 ft. drawdown after 4 hrs. RED CINDERS BROKEN LAVA 480 492 492 HOHEY LEARN LAVA, Blue-Girey Bailer test gal./min. with ft. drawdown after Artesian flow g.p.m. perature of water 5 Depth artesian flow encountered ... 1976 Completed 12-9-1971. Work started 19 7 4 Date well drilling machine moved off of well (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. Well sealed from land surface to ... Diameter of well bore to bottom of seal Date 12-9- 19 76 Diameter of well bore below seal ______in. Number of sacks of cement used in well seal . Drilling Machine Operator's License No. .. Number of sacks of bentonite used in well seal ... Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is ... lbs./100 gals. true to the best of my knowledge and belief. Was a drive shoe used? Tyes No Plugs Size: location ft. Name CulleTT BROS - AKINS

Address

[Signed]

Did any strata contain unusable water?

Yes
No

Was well gravel packed?
Yes No Size of gravel:

Type of water?

Method of sealing strata off

Contractor's License No. 25 2 Date 12-10 1976