LAKE 1034

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

Lake 1034

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED
JUN 3 1975
STATE ENGINEER
SALEM, OREGON

State Well No. 22S/17E-22 d
State Permit No.

(1) OWNER:
Name Tim Puckett-Golden Rule Farms
Address Christmas Valley, Oregon

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☒
4" Diam. from 0 ft. to 70 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " "
" " "
Bailer test 52 gal./min. with 0 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 52° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Portland cement
Well sealed from land surface to 18½ ft.
Diameter of well bore to bottom of seal 17 in.
Diameter of well bore below seal 15 in.
Number of sacks of cement used in well seal 8 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Lake Owner's ~~Driller's~~ well number #5
SE ¼ S ½ Section 22 T. 27-S R. 17-E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 39' ft.
Static level 21' 6" ft. below land surface. Date May 10, 75
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 15" to 180' 8" to 200'
Depth drilled 200 ft. Depth of completed well 200 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Soil, Brown	0	4	
Clay, Green	4	175	21' 6"
Sand, Blk, Coarse-Water bearing	175	185	
Rock, Blk very Hard	185	200	

Work started Feb 27 1975 Completed May 10 1975
Date well drilling machine moved off of well May 10 1975

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Frances F Bigelow (Drilling Machine Operator) Date May 10, 1975
Drilling Machine Operator's License No. 894

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Cunningham Well Drilling (Person, firm or corporation) (Type or print)
Address Box 104 Bend, Ore.
[Signed] Wm. M. Cunningham (Water Well Contractor)
Contractor's License No. 474 Date May 10, 1975

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119