

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

RECEIVED
STATE OF OREGON
(Please type or print)

FEB 23 1980 (Do not write above this line)

State Well No. 276/RE-606

State Permit No. G-9347 #2

(1) OWNER:

Name L. M. Meyer, Jr. SALEM, OREGON

Address PO Box 457 Christina Valley
Oregon 97138

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Other ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☒
14" Diam. from 0 ft. to 97 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations	in. by	in.
perforations from	ft. to	ft.
perforations from	ft. to	ft.
perforations from	ft. to	ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

Flow test 1800 gal./min. with ft. drawdown after 1 hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used cement
Well sealed from land surface to 97 ft.
Diameter of well bore to bottom of seal 16 1/4 in.
Diameter of well bore below seal 12 to 13 ft. then 10"
Number of sacks of cement used in well seal 14 sacks
How was cement grout placed? grout grout.

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Lake Driller's well number 82
NW 1/4 SW 1/4 Section 6 T. 27S R. 18E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 170 ft.

Static level 20 1/2 ft. below land surface. Date Feb 22 80

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 12"-10"

Depth drilled 260 ft. Depth of completed well 260 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
sandy topsoil	0	1	
light brown clay	1	13	
light brown clay	13	24	
disturbances with	24	30	
dark green clay	30	45	
blue green clay	45	55	
green clay	55	170	
white pebbly sand	170	180	
white pebbly sand			
dark green clay	180	225	
white pebbly sand	225	233	
dark green clay	233	255	
white pebbly sand	255	260	
	260		20 1/2

Work started Feb 20 1980 Completed Feb 22 1980

Date well drilling machine moved off of well Feb 22 1980

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Don L. Adams Date Feb 22 80
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1302

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Lyle Adams (Type or print)
(Person, firm or corporation)

Address PO Box 122X Hillbush Ore
97123

[Signed] Lyle Adams (Water Well Contractor)

Contractor's License No. 690 Date Feb 22 1980