NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

Lake 1137 LMW

WATER WELL REPORT

STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED
JAN 17 1977
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 27s/18E-18bc
State Permit No. G-7191 (#3)

(1) OWNER:
Name Jack Gillette
Address Christmas Valley, Ore. 97638

(2) TYPE OF WORK (check):
New Well ☐ Deepening ☒ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED:
Threaded ☐ Welded ☐
..." Diam. from ft. to ft. Gage
..." Diam. from ft. to ft. Gage
..." Diam. from ft. to ft. Gage

(6) PERFORATIONS:
Perforated? ☐ Yes ☐ No.
Type of perforator used
Size of perforations in. by in.
.... perforations from ft. to ft.
.... perforations from ft. to ft.
.... perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☒ Yes ☐ No If yes, by whom? Driller
Yield: 1600 gal./min. with 23 ft. drawdown after 2 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 50° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Well Seal not Disturbed
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☐ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Lake Driller's well number
SW ¼ NW ¼ Section 18 T. 27S R. 18E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 65 ft.
Static level 26 ft. below land surface. Date 12/20/76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 14"
Depth drilled 134 ft. Depth of completed well 414 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Rock, Decomposed	280	288	
Clay, Green Soft	288	315	
Clay, Grey Hard	315	322	
Clay, Green Med.	322	351	
Sand Stone Grey	351	363	
Clay, Green Hard	363	403	
Course Sand + Cinders Black	403	414	26

Work started 11/28 1976 Completed 12/20 1976
Date well drilling machine moved off of well 12/21 1976

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Allen B. Woods (Drilling Machine Operator) Date 1/14, 1977
Drilling Machine Operator's License No. 1015

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Blaylock & Woods Well Drilling (Person, firm or corporation) (Type or print)
Address P.O. Box 2 Silver Lake, Or. 97638
[Signed] Silas Blaylock (Water Well Contractor)
Contractor's License No. 425 Date 1/14, 1977

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119