

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED

MAY 21 1974

State Well No.

STATE ENGINEER

State Permit No.

SALEM, OREGON

275/19E-21

pg 1

bd

(1) OWNER:

Name View Point Ranches
Address Christmas Valley ave.

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven []
Cable [X] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal []
Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:

14" Diam. from 0 ft. to 120 ft. Gage 1/4
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? [] Yes [X] No

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [X] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Baller test 25 gal./min. with 0 ft. drawdown after 3 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used 7 SACKS RAW CEMENT
10 Bottom of Seal
Mixture Cement + Bentonite
Well sealed from land surface to 120 ft.
Diameter of well bore to bottom of seal 17 in.
Diameter of well bore below seal 14 in.
Number of sacks of cement used in well seal 10 sacks
Number of sacks of bentonite used in well seal 10 sacks
Brand name of bentonite Prineville
Number of pounds of bentonite per 100 gallons of water 5.00 lbs./100 gals.
Was a drive shoe used? [X] Yes [] No Plugs 3/8 X 3 Size: location 120 ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County LAKE Driller's well number
SE 1/4 NW 1/4 Section 21 T. 27S R. 19E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 93 ft.
Static level 17 ft. below land surface. Date 2-30-74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 14 in.
Depth drilled 365 ft. Depth of completed well 365 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: Fine Sandy Top soil, hard Brown clay, Soft Grey clay, Soft Blue clay, White Pumace sand, hard Blue clay, Soft Red clay, Fine Grey sand, Soft Grey clay, Fine Pumace sand, Soft Grey clay, Fine Grey sand, Soft Blue clay, Soft Yellow clay, Fine Black sand, Soft Blue clay, Fine Black sand, Soft Blue clay, Fine Grey Pack sand.

Work started 2-25 1974 Completed 5-4 1974
Date well drilling machine moved off of well 5-4 1974

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Silas Blaylock Date 5-19, 1974
(Drilling Machine Operator)
Drilling Machine Operator's License No. 383

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Silas Blaylock (Person, firm or corporation) (Type or print)
Address Sweet Lake ave.
[Signed] Silas Blaylock (Water Well Contractor)
Contractor's License No. 425 Date 5-19, 1974

RECEIVED

WATER WELL REPORT

NOTE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON

MAY 21 1974 State Well No.

(Please type or print)

STATE ENGINEER SALEM, OREGON

State Permit No.

(Do not write above this line)

PG 2

(1) OWNER:

Name
Address

(2) TYPE OF WORK (check):

New Well [] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven []
Cable [] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal []
Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:

Threaded [] Welded []

" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? [] Yes [] No.

Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [] No If yes, by whom?
Well: gal./min. with ft. drawdown after hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? [] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Driller's well number
1/4 1/4 Section T. R. W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found ft.
Static level ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing
Depth drilled ft. Depth of completed well ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Contains handwritten entries for various soil layers like SOFT Blue Clay, Fine Grey Sand, etc.

Work started 19 Completed 19
Date well drilling machine moved off of well 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Date, 19
(Drilling Machine Operator)

Drilling Machine Operator's License No.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name (Person, firm or corporation) (Type or print)

Address

[Signed] (Water Well Contractor)

Contractor's License No. Date, 19