## WATER WELL REPORT STATE OF OREGON

## RECEIVED State Well No. JUL 20 1981

WATER RESOURCES DEPT G-9599

	SALEM, OREGON
(1) OWNER:	(10) LOCATION OF WELL:
Name LAWRENCE IVERSON	County LAKE Driller's well number 1623
Address GEN'L DELIVERY	4 4 Section 18 T. 28 R. 15 E. W.M.
City SILVER LAKE State OR 9763	
(2) TYPE OF WORK (check):	Address at well location:
New Well    Deepening □ Reconditioning □ Abandon □  If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.  Static level ft. below land surface. Date 6-26-31
Rotary Air M Driven	Static level ft. below land surface. Date 6-26-81  Artesian pressure lbs. per square inch. Date
Rotary Mud	10.11
Bored	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel Plastic Threaded Welded	Depth drilled 255 ft. Depth of completed well 285 ft.
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry
	for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
	and indicace principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
	10(50)L 0 1
(6) PERFORATIONS: Perforated? ☐ Yes No	BROWN CLAY 1 20
Type of perforator used	CLAY & GRAVEL PARTICLES 20 28
Size of perforations in. by in.	BUE SANDY CLAY 28 100
perforations from ft. to ft.	CEMENTED GRAVET 100 108
perforations from ft. to ft.	BLACK CIMIDERS 108 150
ft. toft.	BROWN CIMUTES 180 183
(7) SCREENS: Well screen installed?   Yes No	Des CILIDED 9 205 176
Manufacturer's Name	RED CINDERS 265 276  BLACK PACKED SAND 276 285
Type Model No.	BLACK PACKED SANID 276285
Diam. Slot Size Set from ft. to ft.	
Diam. Slot Size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
below static level	
Was a pump test made? ☐ Yes W No If yes, by whom?	
d: gal./min. with ft. drawdown after hrs.	
<i>""</i> " " " " " " " " " " " " " " " " " "	
Air test 10(1) gal./min. with drill stem at 260t. hrs.	
Bailer test gal/min. with ft. drawdown after hrs.	
tesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 6-24- 19 8 Completed 6-26 1981
(9) CONSTRUCTION: Special standards: Yes \( \text{No } \text{L} \)	Date well drilling machine moved off of well 6-26 1981
Well seal—Material used CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of seal in.	and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] Date 114, 1981
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No
How was cement grout placed?	
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge present LLING CO. INC.
Was pump installed?	
Was a drive shoe used? Yes YNo Plugs No. Size: location ft. Did any strata contain unusable water? Yes No. No. 1714 ACY 7253	(Person, firm or corporation) Saturality (Type or print)
Type of Water? depth of strata	Address Lebanon, OR 97355
Method of sealing strata off	[Signed] Sent June
	ATT A THE COLUMN TO THE COLUMN

..... ft. to .....

Size of gravel: .....

Gravel placed from .....

Contractor's License No. Date....