NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the state engineer, salem 10, oregon. TE EIGHT STATE OF OREGON within 30 days from the date of well completion.

OCT 11 WATER WELL REPORT

State Permit No. G-5875

of well completion.	FM. O. CON				
(1) OWNER: Name Delbert Bla	CK	(11) WELL TESTS: Drawd lowere Was a pump test made? The Yes No		1. Pe	<u>ettu</u> s
Address /338 G//-MORE	Yield: 500 gal./min. with 5	6 ft. drawdown	after (hrs.	
SAN LPANDRO CALIFORNIA		"	**		
		15	,,,		
(2) LOCATION OF WELL:		Bailer test gal./min. with	ft. drawdown	after	hrs.
County LAKE Driller's well number BLACK		Artesian flow g.p.m. Date			
1- 14 36 14	28.5 R. 16 E W.M.	Temperature of water 5 Was a ch	emical analysis mad	de? 🗌 Y	es Z No
Bearing and distance from section or subdivision	on corner	(10) THEFT LOC.	of well below casing	- 17"	48"
APPROX. 200' NORTH AND	75 West				-
ROM THE SE CORNE	R OF SECTION	Depth diameter)	of completed well		
2 T 28 S R 16 E W.	M	Formation: Describe by color, characte show thickness of aquifiers and the kin stratum penetrated, with at least one	d and nature of the entry for each char	materio	il in each ormation.
		MATERIAL	F	FROM	TO
(3) TYPE OF WORK (check):	SANDY LOAM, TOP SO	014	0	_5	
w Well		CLAY, BROWN		5	20
		CLAY, BLUE		20	30
	GRAVEL, SMALL, WHITE, HA	PR LEIEL 12	30	45	
(4) PROPOSED USE (check):	(5) TYPE OF WELL:	GRAYEL, SMALL, WHITE , RO		45	75
Domestic Industrial Municipal Rotary Driven Cable Jetted		LAVAROCK, BLAKK, HARD,		75	78_
Irrigation Test Well Other	Dug 🗌 Bored 🗌	RAISED TO 16' at 75	DEPTH.		
(6) CASING INSTALLED: Threaded Welded .		SAND STONE BLACK,		98	100
(ii) CASINO INSTITUTE.	LAVA ROCK, BLACK,		100	120	
14 " Diam. from	WATER LEVEL DROPP	ED TO 22'			
/ Diam. from ft. to	LAVA ROCK, BLACK,		120	125	
Diam, from ft. to	LAVA ROCK BLACK,	POURES	125	165	
(7) PERFORATIONS:	LAVA ROCK, BLACK,	HARD	165	202	
Type of perforator used	WATER LEVEL DROPED TO	, 23			
Size of perforations in. by	LAVA ROCK, BLACK, PO	ures 2	202	225	
perforations from ft. to ft.		CHANGED TO 8" BIT A	17 202		
perforations from	LAVA ROCK, BLACK,		225	262	
perforations from			262	301	
perforations from	WITH SOME CINDERS, SO				
perforations from	LEVEL DROPED TO 24		301	3/5	
	SAND STONE, GREY, HI			320	
(8) SCREENS: Well screen inst	SAND, BLACK, FL	NE	3/5	320	
Manufacturer's Name	Iodel No				
The state of the s		3 Completed 9	- 16	194	
Diam. Slot size Set from Strom Slot size Set from Strom Slot size Set from Strom Str			a	19 6	
Diam. Slot size Set from		Date well drilling machine moved off	or wen		10 62
(9) CONSTRUCTION:		(13) PUMP:			
Well seal—Material used in seal	Manufacturer's Name				
Depth of seal 20 ft. Was a	Type:	н	.P		
Diameter of well bore to bottom of seal					
Were any loose strata cemented off? ☐ Yes ☑ No Depth		Water Well Contractor's Certifica			
Was a drive shoe used? ☐ Yes Z No		This well was drilled under	my jurisdiction a	nd this	report is
	Size of gravel:	true to the best of my knowledge	and bener.		
Gravel placed from ft. to	NAME (JOHN A POTTUS (Person, firm or corporation) (Type or print)				
Did any strata contain unusable water?					
Type of water? Depth of	Address CHRISTMAS VALLEY SUVER LAKE, OL				
Method of sealing strata off	Drilling Machine Operator's Lice	onse No. 28	7		
	O P	12-11-		Marie de la compansa de	
(10) WATER LEVELS:		[Signed]	Vellus	<u>></u>	
Static level 24 ft. below lan	1 (/ 1101	ater Well Contractor)	471	10/:	
Artesian pressure lbs. per so	Contractor's License No. 4.0.1.	Date J.J.	1-4	, 19.4?	