

NOTICE TO WATER WELL CONTRACTOR: The original and first copy of this report are to be filed with the

RECEIVED

WATER WELL REPORT, see rate attached. State Well No. 285/16E-11AC

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days of the date of well completion. WATER RESOURCES DEPT. SALEM, OREGON

STATE OF OREGON (Please type or print) attached. State Well No. 285/16E-11AC State Permit No. G-10044

(1) OWNER: Name Mrs. Renate Wolfstrom Address PO Box 132 Silver Lake, Ore 97638

(2) TYPE OF WORK (check): New Well Deepening Reconditioning Abandon If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: Rotary Cable Dug Driven Jetted Bored (4) PROPOSED USE (check): Domestic Industrial Municipal Irrigation Test Well Other

CASING INSTALLED: 12" Diam. from 0 ft. to 43 ft. Gage 250

PERFORATIONS: Perforated? Yes No. Type of perforator used Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS: Well screen installed? Yes No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to

(8) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? Yes No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs.

(9) CONSTRUCTION: Well seal—Material used cement Well sealed from land surface to 4 ft. Diameter of well bore to bottom of seal 15 in. Diameter of well bore below seal 12" to 100 in - 8" Number of sacks of cement used in well seal 20 How was cement grout placed? pressure grouted

Was a drive shoe used? Yes No Plugs Size: location ft. Did any strata contain unusable water? Yes No Type of water? depth of strata Method of sealing strata off Was well gravel packed? Yes No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL: County Lake Driller's well number 46 SW 1/4 NE 1/4 Section 11 T.285 R. R16E W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well. Depth at which water was first found 133 ft. Static level 23 ft. below land surface. Date May 12-79 Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 12" - 8" Depth drilled 250 ft. Depth of completed well 250 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top soil	0	1	
Brown clay	1	10	
Light brown clay	10	39	
broken basalt & clay	39	72	
Basalt partial broken	72	72	
broken basalt	72	76	
Grey basalt hard	76	85	
broken basalt	85	87	
hard basalt grey	87	94	
Broken red hard	94	98	
Grey basalt hard	98	101	
Grey brown basalt	101	105	
Grey basalt	105	139	
Grout red cinder analysis (water bearing)	139	140	23
They cinders aquifer	140	148	
Red & brown cinder	148	188	
Grey basalt	188	247	
broken grey basalt	247	250	

Work started May 10 1979 Completed May 12 1979 Date well drilling machine moved off of well May 14 1979

Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Stan Adams (Drilling Machine Operator) Date May 13, 1979 Drilling Machine Operator's License No. 1302

Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Lyle R. Adams (Person, firm or corporation) (Type or print) Address Rt 3 Box 122X Silver Lake Ore 97123 [Signed] Lyle R. Adams (Water Well Contractor) Contractor's License No. 690 Date May 12, 1979

Lyle Adams

RECEIVED

MAY 22 1979

WATER RESOURCES DEPT.
SALEM, OREGON

Dear Sirs

I made a mistake on well sealed land surface
to 4 ft. (supposed to be 43 ft.) on Mrs. Renata Wolfstrom's log
my no 46 well
location Lake Co SW $\frac{1}{4}$ of NE $\frac{1}{4}$ Sec. 11 T28S R16E