filed with the MAR 13 1972 STATE OF	L REPRECEIVED OREGON APR3-1972 tate Well No. 28/16-12ac
STATE ENGINEER, SALEM, OREGON 97310	or prinSTATE ENGINEER No. G-5497
- Wasan	(10) LOCATION OF WELL:
(1) OWNER:	
Name WAYNE HOLLINGSWORTH	County LAKE Driller's well number
Address RT2 Box 364	SW 14 NF 14 Section /2 T. 285 R.   6 E W.M.
VENETA ONE GON	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well ☐ Deepening Abandon ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Rotary Driven Domestic Industrial Municipal D	Static level 57 ft. below land surface. Date 2-20-72
Cable  Jetted	Artesian pressure lbs. per square inch. Date
Dug Bored Irrigation Test Well Other	THE PROPERTY OF THE PROPERTY O
CASING INSTALLED: Threaded  Welded	(12) WELL LOG: Diameter of well below casing
ft. Gageft.	Depth drilled 40 ft. Depth of completed well 181 ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated,
THE TOP A WIGNE	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
PERFORATIONS: Perforated?   Yes   No.	
Type of perforator used	MATERIAL
Size of perforations in. by in.	REAMED 6 /2 IN. HOLE-
perforations from ft. to ft.	- TO 8 /N. MOLE TO LIVE PT
perforations from ft. to ft.	-F-KOM100F1, [0/41 F1
perforations from ft. to ft.	DEMONISTRA MODAL EVIDE
(7) SCREENS: Well screen installed?   Yes   No	TO 18) FT. WITH 8 IN.
Manufacturer's Name	COEV INVA VIII IEL
Type Model No	OF A JAVA JOJAKA
Diam.         Slot size         Set from         ft. to         ft.           Diam.         Slot size         Set from         ft. to         ft.	RED BROKEN LAVA 162 181
Diam. Slot size Set from 11. to 11.	The University of the state of
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made?  Yes No If yes, by whom?	.=
Yield: gal./min. with ft. drawdown after hrs.	
" " " " " " " " " " " " " " " " " " " "	
n n n n n n n n n n n n n n n n n n n	
Bailer test // gal./min. with 0 ft. drawdown after 1 hrs.	
Artesian flow g.p.m.	
Depth artesian flow encountered ft.	Work started 10 - 15 197/ Completed 2 - 20 1972
(9) CONSTRUCTION:	Date well drilling machine moved off of well 2 - 20 19 22  Drilling Machine Operator's Certification:
Well seal—Material used	This well was constructed under my direct supervision.
Well sealed from land surface toft.	Materials used and information reported phove are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief
Diameter of well bore below sealin.	Firthing Michine Officiation 11
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 383
Number of sacks of bentonite used in well seal sacks	
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of waterlbs./100 gals	true to the best of my knowledge and belief.
Was a drive shoe used?   Yes  No Plugs Size: location ft.	
Did any strata contain unusable water?  Yes  No	TO A SUVER LAKE OR
Type of water? depth of strata	Address Address
Method of sealing strata off	[Signed] Signed]
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Collitractor)
Gravel placed fromft. toft.	Contractor's License No. 4. 3. 5. Date 3 7. 19.72