

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED WATER WELL REPORT NOV 21 1969 STATE ENGINEER SALEM, OREGON

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Please type or print) not write above this line

State Well No. 28/16-12ac State Permit No. G-5497

Lake 1393 77 G50

(1) OWNER:

Name WAYNE HOLLINGSWORTH Address R2 BOX 364 VENETA ORE.

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven [] Cable [] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [X] Test Well [] Other []

CASING INSTALLED:

12" Diam. from 0 ft. to 20 ft. Gage 1/4 IN. Threaded [] Welded [X]

PERFORATIONS:

Perforated? [] Yes [X] No

Type of perforator used

Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 57 ft. below land surface Date 11-15-69 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [X] No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs.

Bailer test 100 gal./min. with 0 ft. drawdown after 3 hrs. Artesian flow g.p.m. Date Temperature of water Was a chemical analysis made? [] Yes [] No

(10) CONSTRUCTION:

Well seal—Material used CEMENT + BENONITE Depth of seal 20 ft. Diameter of well bore to bottom of seal 16 in. Were any loose strata cemented off? [] Yes [X] No Depth Was a drive shoe used? [] Yes [X] No Did any strata contain unusable water? [] Yes [X] No Type of water depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County LAKE Driller's well number SW 1/4 NE 1/4 Section 12 T. 28 S. R. 16 E W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

FIRST 100 FT. 12 IN. Diameter of well below casing LAST 41 FT. 6 IN. Depth drilled 141 ft. Depth of completed well 141 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include SANDY LOAM, HARD BROWN CLAY, HARD GREY LAVA ROCK, BROKEN RED LAVA ROCK, GREY LAVA ROCK.

Work started 7-1 1969 Completed 11-15 1969 Date well drilling machine moved off of well 11-20 1969

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Silas Blaylock Date 11-20, 1969 (Drilling Machine Operator)

Drilling Machine Operator's License No. 383

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME SILAS BLAYLOCK (Person, firm or corporation) (Type or print)

Address SILVER LAKE OREGON

[Signed] Silas Blaylock (Water Well Contractor)

Contractor's License No. 425 Date 11-20, 1969