FEB9 1981

TER WELL REISTATE OF OREGON JAKE WATER WELL REPORT

WATER RESOURCES DEPT SALEM, OREGON

State Well No.	265-	16€	- 14	6-0

State Permit No.	*****************************
	•

\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
(1) OWNER:	(10) LOCATION OF WELL:
Name Wayne Stutzman	County Lake Driller's well number 134
Address BH 545	5 W 47 W 4 Section 14 T 265 R 16 F W.M.
City Christian Valley State Ou 97638	Tax Lot # Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location:
New Well	(11) WADDED I EVIDI - Completed
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 94 ft. Static level 43 ft. below land surface. Date
Rotary Air Driven Domestic I, Industrial Municipal .	Static level 4 ft. below land surface. Date 177 Jan, Artesian pressure lbs. per square inch. Date
Rotary Mud Dug	
Cable 1 2000	Depth drilled 1.56 Diameter of well below casing
CASING INSTALLED: Steel Plastic W	Formation: Describe color, texture, grain size and structure of materials; and show
"Diam from O ft. to ft. Gauge	thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level
"Diam from ft. to ft. Gauge	and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
"Diam from ft. to ft. Gauge	brown Sand and Boulders 0 5
	Brown clay 5 65
(6) PERFORATIONS: Perforated? □ Yes ☑ No Type of perforator used	Green Brown shale 65 79
Size of perforations in. by in.	Gray Basalt-hard 79 94
perforations from	orech shalf 7/B 1 94 95 43
perforations from	Green Shales lava W/1 122 124 43
perforations from ft. to ft.	Gray basalt-hard 124 133
(7) SCREENS: Well screen installed? Yes No	Brown green shale w/B 133 155 93
Manufacturer's Name	Gray basalt -hard 155 156
Type	bray basa (+ - hard 155 156
m. Slot Size Set from ft. to	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made?	
Yield: gal/min. with ff. drawdown after hrs.	
" " ".	
And test 250 gal/min. with drill stem at 156 ft. hrs.	
Bailer test gal/min. with ft. drawdown after hrs.	
Artesian flow g.p.m. Temperature of water Depth artesian flow encountered ft.	1 1 2 2 2
	Work started Gran Dec 3 (19 8 Completed Tan 19 8 Date well drilling machine moved off of well Tan 19 8
(9) CONSTRUCTION: Special standards: Yes \(\text{No} \)	
Well sealed from land surface to	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of seal	and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] Aton I Date Jam 1981.
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 130.2
How was cement grout placed? NESSUVE growted	
The state of the s	Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to
Was pump installed?TypeHPDepthft.	the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes No Plugs	Name July Character (Cype or print)
Did any strata contain unusable water? Yes No	Address DOX 467 Chiralmas Willey OVR 99639
Type of Water? depth of strata	1 Telogram of The along 2
Method of sealing strata off	[Signed] Sycotton (Water Well Contractor)
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	Contractor's License No. 6.7.2Date
Gravel placed fromft. toft. NOTICE TO WATER WELL CONTRACTOR	WATER RESOURCES DEPARTMENT, SP*12658-690
The original and first copy of this report	SALEM, OREGON 97310
are to be filed with the	within 30 days to day of well