NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

are to be filed with the

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the day
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No. 256/15E-33
State Permit No. G-8572 #2

(1) OWNER:	(10) LOCATION OF WELL:
Name Alfred Roberts	County Lake Driller's well number
Address Fort Rock, Or. 97638	14 14 Section 33 T. 255 R. 15 E. W.M.
(A) WYDD OD WODY (1. I)	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon A	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 102 ft.
Rotary W Driven Domestic Industrial W Municipal Domestic	Static level 38 ft. below land surface. Date 8-20-7
Dug 🔲 Bored 🔲 Irrigation 🗎 Test Well 🗍 Other 🗍	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: 15 Threaded Welded V. Threaded to the Gage 250.	(12) WELL LOG: Diameter of well below casing
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
PERFORATIONS: Perforated? Yes No.	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Brown Clary 0 42
perforations fromft. toft.	Green Stone 42/25
perforations from ft. to ft.	Brown Lava Rock 125 132
perforations from ft. to ft.	Blue Inon Rock 132 280
(7) SCREENS: Well screen installed? Yes No	Water garing
Manufacturer's Name Model No	55658263
Diam Slot size Set from ft. to ft.	ALULIVED
Diamft. toft.	AUG 2 0 1979** **
(8) WELL TESTS: Drawdown is amount water level is	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	WATER RESOURCES DEPT
Was a pump test made? Yes No If yes, by whom?	SALEM, OREGON
Yield: gal./min. with ft. drawdown after hrs.	
" " " " " " " " " " " " " " " " " " "	
Bailer test 900 gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	To the second se
perature of water Depth artesian flow encounteredft.	Work started 7-23 1974 Completed 8-70 1979
	Date well drilling machine moved off of well 8-20 1976
(9) CONSTRUCTION:	
Well seal-Material used Cement	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Well sealed from land surface toft.	Materials used and information reported above are true to my
Diameter of well bore to bottom of seal	best knowledge and belief.
Number of sacks of cement used in well sealsacks	[Signed] Date 1 197
How was cement grout placed?	Drilling Machine Operator's License No. 694
Cerent was Mexed up. Diperun	Water Well Contractor's Certification:
down lows side of the easingt	
presher growted an	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes 🐧 No Plugs Size: location	Name Mel Sear & Well Orilling (Type orderint)
Type of water? depth of strata	Address P.O. Box 432 Lehanon Or.
Method of sealing strata off	Million Jana
Was well gravel packed?	[Signed] (Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 567. Date 8-26, 19.79