are to be filed with the	
WATER RESOURCES DEPARTMENT, OCT 2.1 1908TATE OF OREGON / State Well No S	
SALEM, OREGON 97310 Within 30 days from the daWATER RESOURCES DEPT of well completion. SALEM OREGON	pe or print)
of well completion. SALEM, OREGON	above this line) State Permit No.
(1) OWNER:	(10) LOCATION OF WELL:
Name Ebances Allen	
Address OPED A Ranch	The state of the s
Lakeview ORE. 97630	NW 4 NE 4 Section 29 T. 375 R. 20 E W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL C. 1 / 1
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well. Depth at which water was first found 40
Driven Domestic Industrial Municipal	Static level 24 ft. below land surface. Date 6 17 190
Dug ☐ Bored ☐ Irrigation 🔀 Test Well ☐ Other ☐	
(5) CASING INSTALLED: Threaded Welded W	(19) YEST TOO
14 "Diam. from +1 tt. to 139 tt. Gage 250	(12) WELL LOG: Diameter of well below casing
" Diam. from ft. to ft. Gage	it. Depth of completed well
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
(6) PERFORATIONS: Perforated? I Vos. by No.	with at least one entry for each change of formation Report each change in
Type of perforator and	position of Static Water Level and indicate principal water-bearing strata.
Size of perforations in. by in.	MATERIAL From To SWL
perforations fromft. toft.	100 201
perforations from	Large Cobbles 4 gravel 5 10
perforations from ft. to ft.	Sand Gravel 10 60
(7) CODERAG	FREE RUN SANDERAUEL 60 100
wen sereen matanedr Li res 12 No	Sandy brown Clau Stone 130 144
Manufacturer's Name	Brown clay store 144 208 24
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is	
lowered below static level	
a pump test made? Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	SEP 2 9 1980
II	WATER RESOURCES DEPT
er test 200 gal./min. with 0 ft. drawdown after / hrs	SALEM, OREGON
er test 200 gal./min. with ft. drawdown after hrs.	
Artesian flow g.p,m.	
Temperature of water Depth artesian flow encounteredft.	Work started 5/23 19 40 Completed 6/17 1940
(9) CONSTRUCTION:	Date well drilling machine moved off of well (0 17 1940
Well seal—Material used <u>Cement</u>	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below sealin.	[Signed] Larry Chancello Date 6 17, 1980
Number of sacks of cement used in well seal	(Drilling Machine Operator) Drilling Machine Operator's License No
pacer:	Machine Operator's License No.
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief. Name Sever 1, 19 1 3 2 1 1 10 4
Did any strata contain unusable water? Tyes 💆 No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address NORth & LKV 97630
Method of sealing strata off	[Signed] Len J. Coney
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 6 Date 6 17 , 19.40
(USE ADDITIONAL SUI	

The original and first copy of this report E C WATER WELL REPORT