NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT ECEIVED

STATE OF OREGON

FEB 17 19state Well No.

(Please type or print) WATER RESOURCE Bte Dept No. 6-9882 (Do not write above this line) SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:				
Name C. F. Enloe	County Lake Driller's well no		-		
Address Rte. 6, Box 160	NE 14 Section 26 T. 385	_{R.} 19	<u></u>	W.M.	
Lakeview, Oregon 97630	Bearing and distance from section or subdivision	on corner			
(2) TYPE OF WORK (check):					
New Well					
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found			ft.	
Rotary Driven Domestic Industrial Municipal	Static level 48 ft. below land s	urfoos T	10to /2	1-197	
Jetted Irrigation	20. 201017 2010				
(5) CASING INSTALLED: Threaded Welded 250 12 " Diam. from 0 ft. to ft. Gage 250	(12) WELL LOG: Diameter of well below casing Depth drilled 800 ft. Depth of completed well 800 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in				
(6) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	.cipai wate	r-bearin		
Type of perforator used factory Size of perforations 1/8 in. by 2½ in.	MATERIAL	From	То	SWL	
and or porter and an arrangement and arrangement arrangement are a second arrangement are a seco	Top Soil	0	4	48	
17.760 perforations from 60 ft. to 800 ft.	Cement Gravel	4	80	40	
perforations from ft. to ft.	Sandy Clay	80	139	1.0	
perforations from ft. to ft.	Green - Black Clay	1 39	260	48	
(7) SCREENS: Well screen installed? Yes No	Light Green Clay	260 451	451		
Manufacturer's Name	Cement Gravel & Sand	451	513		
Type Model No.	Pumice Sand with Streaks	513	600		
Diam. Slot size Set from ft. to ft.	of Clay Hard Sand	600	61 5		
Diam. Slot size Set from ft. to ft.	Varied Color Clays	61 5	743		
	Pumice Sand & Clay	743	800	48	
Transform is amount water level is lowered below static level. Interstate Co. Yield: 1100 gal./min. with 52 ft. drawdown after 15 hrs.	RECEIVEL AUGO 11980				
n n h n					
	WATER RESOURCES DI	EPT			
Refer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m.	SALEM. OREGON	-			
Temperature of water Depth artesian flow encountered ft.	Work started Nov 19 79 Complete	ed 8/8		19 79	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	8/8		¹⁹ 79	
Well seal—Material used	Drilling Machine Operator's Certification: This well was constructed under my Materials used and information reported best knowledge and belief. [Signed] (Drilling Machine Operator) Drilling Machine Operator's License No.	above and Date $\frac{8}{3}$	re true	to my	
prosure grown	Water Well Contractor's Certification:				
	This well was drilled under my jurisdi	ction and	l this r	eport is	
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and beli	ief.			
Did any strata contain unusable water? Yes No	Name C & C Enloe Drilling (Person, firm or corporation)	(Tvr	e or prin	at)	
Type of water? depth of strata	Address P.O. Box 323, Dorris,				
Method of sealing strata off	10,001 61	*************	**********	***********	
Was well gravel packed? Yes □ No Size of gravel: 3/8-3/4	[Signed] (Water Well Contr.	actor)		Whitehannesers :	
Gravel placed from 35 ft. to 800 ft.	د عددي بو دست کاليوان د مود دار	8/9		1979	

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

State Well No. 388/1915 -26a State Permit No.

of well completion.	Do not write ab	ove this line)	G -	888	2	
(1) OWNER:		(10) LOCATION OF WELL:				
Name C. F. ENloe		County LAKe Driller's well number				
Address Rt L. Bal 160						
LAKEVIEW One.	-	NE 34 34 Section 26 T. 385 R. 192 W.M. Bearing and distance from section or subdivision corner				
(2) TYPE OF WORK (check):		bearing and distance from section or su	bdivision corne	er		
New Well Deepening Reconditioning	Abandon 🔲		,			
If abandonment, describe material and procedure in Item 12.		(11) WAMED LEVEL, Completed well				
(3) TYPE OF WELL: (4) PROPOSED USE	(check):	(11) WATER LEVEL: Completed well.				
Rotary EV Driven D		Depth at which water was first found ft.				
Cable		Static level 48 ft. below land surface. Date				
Dug District Hilligation & Test wen	Outer []	Artesian pressure lbs. per	square inch.	Date		
——————————————————————————————————————	đeđ □	(12) WELL LOG: Diameter of well below casing				
	e :250	Depth drilled 800 ft. Depth of completed well 800 ft.				
"Diam. from, ft. to ft. Gag	e	Formation: Describe color, texture, grain size and structure of materials;				
" Diam. from ft. to ft. Gag	(e	and show thickness and nature of each stratum and aquifer penetrated				
PERFORATIONS: Perforated? Yes	□ No	with at least one entry for each change of position of Static Water Level and indica				
Type of perforator used factory		MATERIAL	From	то	swL	
Size of perforations 18 in. by 2/2 in.		top Soil	. 0	41		
perforations from SCC ft. to	et	Cement Gravel	4	80'	48	
17,760 perforations from 60 ft. to 86		Sandy Clay	80	139		
perforations from ft. to		Kheen + Black Clay	139	260	48	
(E) CODERNIC.		Light Green clay	260	451		
(7) SCREENS: Well screen installed? ☐ Yes	<u>~</u> No	Cement Gravel + Send	451	513		
Manufacturer's Name Model No.	********************	pumice Sand With Stra		2 .		
Diam. Slot size Set from ft. to		of Clay Ward Sand	518	600		
Diam. Slot size Set from ft. to	1	Varied Color Clays	600	743		
		Pamier Sank + clay	743	800	48	
(8) WELL TESTS: Drawdown is amount water lowered below static level	trite purup	OFFINED				
Was a pump test made? Yes \(\subseteq \) No If yes, by whom?	Co					
Yield: //00 gal./min. with 52 ft. drawdown after	er 15 hrs.	AUS 2.0 1979				
<i>n</i>	.#	WATER RESOURCES DEP	<u></u>			
" "	,,,	SALEM, OREGON	1		-	
Bailer test gal./min. with ft. drawdown as	fter hrs.	DALLIN, UNLEUT,		1		
Artesian flow g.p.m.	-			<u> </u>	<u> </u>	
perature of water Depth artesian flow encountered	#1	Work started NN 1978 C	ompleted CL	10	1979	
postario de maior de partir de la constante de	201			Tr.		
(9) CONSTRUCTION:		Date well drilling machine moved off of	wen aug	-	1971	
Well seal—Material used Kement	************************	Drilling Machine Operator's Certific				
Well sealed from land surface to 351	ft.	This well was constructed unde Materials used and information rep				
Diameter of well bore to bottom of seal 20 in.		best knowledge and belief.	,	. 1 .	عد وسند	
Diameter of well bore below seal		[Signed] (Drilling Machine Operator) Date 8/1, 1979				
Number of sacks of cement used in well seal How was cement grout placed?		Drilling Machine Operator's License No. 316				
now was cement grout praced?	,					
		Water Well Contractor's Certification				
	***********************	This well was drilled under my jurisdiction and this report is				
Was a drive shoe used? Yes No Plugs Size: loca	tion ft.	true to the best of my knowledge and belief.				
Did any strata contain unusable water? Yes No		(Person, firm or corporation) (Type or print)				
Type of water? depth of strata		Address P.U. Bry 323 Dom	ris Ca. 9	6023	}	
Method of sealing strata off		[Signed] Las W. Enla	_			
Was well gravel packed? ✓ Yes ☐ No Size of gravel	18-3/4	(Water We	11 Contractor)		************	
Gravel placed from 35' ft. to 800 ft.	_	Contractor's License No. 503 Da	ite 8/9		, 19.7.9	