NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No. 395/196-14

State Permit No. ....

(1) OWNER:	(10) LOCATION OF WELL:			
Name Ed Wiebe	County Lake Driller's well number 12			
Address Route 6	. 1/4 Section 30 T 10 R 14 W.M.			
Lakeview, Oregon 97630	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):				
New Well 🕻 Deepening 🗌 Reconditioning 🗍 Abandon 🗆				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 50 ft.			
Rotary   Driven   Domestic 😿 Industrial   Municipal	Static level 2 ft. below land surface. Date 6/20/79			
Bored   Irrigation   Test Well   Other	Artesian pressure			
(5) CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing  Depth drilled 295 ft. Depth of completed well 289 ft.			
" Diam. from ft. to ft. Gage " Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratu with at least one entry for each change of formations of Static Water Versions and interest one strate with the state of	m and a tion, Rep	quifer pe	enetrated, change in
(6) PERFORATIONS: Perforated? Yes No.  Type of perforator used Pre-perforated	position of Static Water Level and indicate prin	From	то	SWL
Size of perforations 1/8 in. by 3 in.	Top Soil	0	3	
246 perforations from 43 ft. to 289 ft.	Sand coarse (brown)	3	50	
perforations fromft. toft.	Sand Black with gravel	50	82	
perforations fromft. toft.	fine & clay			
	Clay	82	100	
(7) SCREENS: Well screen installed?   Yes   No	Sand (black)	100	140	
Manufacturer's Name	Sand cemented (black)	140	240	: 
Type Model No.	and gravel	01.0		<del></del>
Diam.       Slot size       Set from       ft. to       ft.         Diam.       Slot size       Set from       ft. to       ft.	Sand (water)	240	295	
Diant, Stot size Set from 11.		<del>                                     </del>		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level  y a pump test made? □ Yes ☒ No If yes, by whom?	RECEIVED			
Yield: gal./min. with ft. drawdown after hrs.	AUGO 1 1980			
" " "	WATER RESOURCES DEP	Γ		
	SALEM, OREGON			
Bailer test gal./min. with ft. drawdown after hrs.	I THE STATE OF THE			<u> </u>
Sian flow g.p.m.		<u> </u>	<u> </u>	
Temperature of water Depth artesian flow encountered ft.	Work started 6/9/79 19 Complete			19 79
(9) CONSTRUCTION:	Date well drilling machine moved off of well	6/2	0	<sup>19</sup> 79
Well seal—Material used Cement  Well sealed from land surface to 40 ft.  Diameter of well bore to bottom of seal 16 in.  Diameter of well bore below seal 8 in.  Number of sacks of cement used in well seal 42 sacks  How was cement grout placed? Pumped in well  with grout pump	This well was constructed under my Materials used and information reported best knowledge and belief.  [Signed] (Drilling Machine Operator)  Drilling Machine Operator's License No.  Water Well Contractor's Certification:	direct above Date	are true	to my
113 TO 1 T	This well was drilled under my jurisdi	iction a	nd this r	eport is
Was a drive shoe used? ☐ Yes 🍱 No Plugs Size: location ft.	true to the best of my knowledge and belief.			
Did any strata contain unusable water? 🗌 Yes 🛣 No	Name C & C Enloe Drilling (Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address P.O. Box 323, Dorris,		96023	
Method of sealing strata off	Isimal Pull Enlan	_		
Was well gravel packed?   Ves □ No Size of gravel: 3/8-3/4	[Signed] (Water Well Contr	actor)		
Gravel placed from 40 ft. to 289 ft.	Contractor's License No. 503 Date	6/30		1979