NOTICE TO WATER WELL CONTRACTOR The original and first copy

of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

WATER WELL REPORT CELVE

STATE OF OREGON

(Please type or print)

AUG 27 1976 State Permit No. 3/5,

(Do not write above this line) RESOURCES DEPT.

	(10) LOCATION OF WELL:		
(1) OWNER:		iher .	
Name ADEL SCHOOL DIST # 2	20 mg	.24	W.M.
Address ADEL OR.	JW 15 12 12	and the second	
Address the the the test of th	Bearing and distance from section or subdivision	corner	X
(2) TYPE OF WORK (check):	180' South From NE Cor	ner	·
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	11.	
			ft.
(6) 222	mm at helem land out	rface. Date 8_	21_76
Rotary Driven Domestic Industrial Municipal Cable Jetted D		inch Date	
Cable 25 Jetted ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square	Incii. Date	
The state of the s	(12) WELL LOG: Diameter of well be	low enging	611
CASING INSTALLED: Threaded Welded \(\)		How cashing	7 ft.
6 "Diam. from 0 ft. to 150 ft. Gage . 250	Depth drilled 157 ft. Depth of comple		
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size at and show thickness and nature of each stratum	nd structure of and aquifer r	materiais; enetrated,
"Diam. fromft. Gage			
A PROPERTY A PROPERTY OF THE P	position of Static Water Level and indicate princ	ipal water-bear	ing strata.
PERFORATIONS: Perforated? Yes No.	MATERIAL	From To	swL
Type of perforator used	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0 7	
Size of perforations in. by in.	Top Soil Brown	7 10	
perforations fromft. toft.	Clay Grey	10 21	1
perforations from ft. to ft.	Clay Sandy Grey	27 40	
perforations from ft. to ft,	Clay Grey	40x 47	
	Sand Grey fine	47 88	
(7) SCREENS: Well screen installed? Yes X No	Clay Blue	88 98	88
Manufacturer's Name	Sand White Fine (Water)	98 101	100
TypeModel No.	Clay Blue		75
Diam. Slot size Set from ft. to ft.	Sand Blue Coarse (Water)	 1 1 1 1 1 1 1 1 1 	1-13-
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Yes No If yes, by whom?			
wield: gal /min, with ft. drawdown after hrs.			
neut.			-
The state of the s		†	-
" To state the state of the sta			
Bailer test 15 gal./min. with 10 ft. drawdown after 1 hrs.	2		
Artesian flow g.p.m.	0 C 1076 Complete	ed 8	21 1976
mperature of water 4 Depth artesian flow encounteredft.	Work started 8-6 1976 Complet	8-21	1976
(a) CONCERNICATION.	Date well drilling machine moved off of well	<u> </u>	19 (0
(9) CONSTRUCTION:	Drilling Machine Operator's Certification	:	
Well seal-Material used Cement	mile week constructed under my	, direct sup	ervision.
Well sealed from land surface to	Materials used and information reported best knowledge and belief.	. above are u	140 00 113
Diameter of well bore to bottom of sealin.	T YOUR WALL X NO. 19 MAY	Date 8-21	L 19.76
Diameter of well bore below seal	(Drilling Machine Operator)		······································
Number of sacks of cement used in well seal 14 sack	Drilling Machine Operator's License No.	195	
Number of sacks of bentonite used in well seal sack			
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is		
of waterlbs./100 gale			
Was a drive shoe used? A Yes No Plugs Size: location f	Name SEVEY WELLDRILLING (Person, firm or corporation)	(Type or	print)
Did any strata contain unusable water? Yes X No		_	
Type of water? depth of strata	Address 117 North K. Lky. Or.		
Method of sealing strata off	[Signed] Alen T	ay_	
Was well gravel packed? ☐ Yes 집 No Size of gravel:	(water wen con	~	
Crowd placed from	Contractor's License No. 617 Date	8_21	, 19.7.
CINOTOL DIODOC TROTT			