

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the
WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER RESOURCES DEPT.
STATE OF OREGON
(Please type or print)
(Do not write above this line)
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 405/19e-3266
State Permit No.

(1) OWNER:

Name Thomson & Cox
Address Lakeview, Ore.

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

CASING INSTALLED:

12" Diam. from 0 ft. to 240 ft. Gage 1/2"
10" Diam. from 235 ft. to 295 ft. Gage 1/2"
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☒ Yes ☐ No.

Type of perforator used factory

Size of perforations 3/16 in. by 3 in.
-50' perforations from -5 ft. to 295 ft.
perforations from 50 ft. to 295 ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☒ Yes ☐ No If yes, by whom? pump co.

Yield: 620 gal./min. with 120 ft. drawdown after 12 hrs.

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water 54 Depth artesian flow encountered 70 ft.

(9) CONSTRUCTION:

Well seal—Material used cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 16 in.
Diameter of well bore below seal 12 in.
Number of sacks of cement used in well seal 16 sacks
How was cement grout placed? poured from top

Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Lake Driller's well number
N.W. N.W. 1/4 Section 32 T40S R. 19E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 70 ft.
Static level ft. below land surface. Date
Artesian pressure 1 lbs. per square inch. Date 8/1/78

(12) WELL LOG:

Diameter of well below casing 10

Depth drilled 300 ft. Depth of completed well 290 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Yellow clay	0	22	
blue clay & sand	22	34	
gray clay	34	46	
gray sand	46	72	0
gray clay	72	84	0
layers of sand & clay	84	140	0
gray sand	140	147	0
gray clay & sand layers	147	188	0
gray sand	188	218	0
blue clay	218	265	0
gray sand	265	272	0
gray clay	272	276	0
gray clay & sand layers	276	295	0
gray clay	295	300	0

Work started 6/1 19 78 Completed 7/26 19 78

Date well drilling machine moved off of well 7/26 19 78

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

(Signed) George M. Baber Date 8/1, 19 78
(Drilling Machine Operator)

Drilling Machine Operator's License No. 654

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name John A. Van Meter

(Person, firm or corporation) (Type or print)

Address P.O. Box 204 Malin, Ore.

(Signed) John A. Van Meter
(Water Well Contractor)

Contractor's License No. 170 Date 8/1, 19 78

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date
of well completion.

6-12510

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

WATER RESOURCES DEPT.

State Well No.

State Permit No.

405/19E-32

(1) OWNER:

Name Thomson & Cox

Address Lakeview, Ore.

SALEM, OREGON

(10) LOCATION OF WELL:

County X Lake

Driller's well number

N.W. 1/4 Section 32

T40S R. 19E

W.2

Bearing and distance from section or subdivision corner

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☒

12" Diam. from 0 ft. to 240 ft. Gage 1"

20" Diam. from 235 ft. to 295 ft. Gage 1"

" Diam. from ft. to ft. Gage "

(6) PERFORATIONS:

Perforated? ☒ Yes ☐ No.

Type of perforator used factory

Number of perforations 3/16 in. by 3 in.

50' perforations from -5 ft. to ft.

perforations from 50 ft. to 295 ft.

perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level.

Was a pump test made? ☒ Yes ☐ No If yes, by whom? pump co.

Yield: 620 gal./min. with 120 ft. drawdown after 12 hrs.

" " " "

" " " "

" " " "

Artesian flow g.p.m.

Temperature of water 54 Depth artesian flow encountered 70 ft.

(9) CONSTRUCTION:

Seal—Material used cement

Well sealed from land surface to 20 ft.

Diameter of well bore to bottom of seal 16 in.

Diameter of well bore below seal 12 in.

Number of sacks of cement used in well seal 16 sacks

How was cement grout placed? poured from top

Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(11) WATER LEVEL: Completed well.

Depth at which water was first found 70

Static level ft. below land surface. Date

Artesian pressure 1 lbs. per square inch. Date 8/1/78

(12) WELL LOG:

Diameter of well below casing 10

Depth drilled 300 ft. Depth of completed well 290 ft

Formation: Describe color, texture, grain size and structure of materials and show thickness and nature of each stratum and aquifer penetrated with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata

MATERIAL	From	To	SWL
Yellow clay	0	22	
blue clay & sand	22	34	
gray clay	34	46	
gray sand	46	72	0
gray clay	72	84	0
layers of sand & clay	84	140	0
gray sand	140	147	0
gray clay & sand layers	147	188	0
gray sand	188	218	0
blue clay	218	265	0
gray sand	265	272	0
gray clay	272	276	0
gray clay & sand layers	276	295	0
gray clay	295	300	0

Work started 6/1 19 78 Completed 7/26 1978

Date well drilling machine moved off of well 7/26 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

(Signed) George M. Barber Date 8/1, 1978
(Drilling Machine Operator)

Drilling Machine Operator's License No. 654

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name John A. Van Meter

(Person, firm or corporation)

(Type or print)

Address P.O. Box 204 Malin, Ore.

(Signed) John A. Van Meter
(Water Well Contractor)

Contractor's License No. 170 Date 8/1, 1978