

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED

DEC 19 1978

App G-11307
4/5/20E-24ca
State Well No.
State Permit No.

WATER RESOURCES DEPT.

(1) OWNER:

Name Paul Thill
Address New Pine Creek OR

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☒
" Diam. from 0 ft. to 1.5 ft. Gage 250

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

of perforator used

Size of perforations in. by in.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " "

" " " "

Bailer test 10 gal./min. with 25 ft. drawdown after 1 hrs.

Artesian flow g.p.m.

Temperature of water 54 Depth artesian flow encountered ft.

CONSTRUCTION:

Well seal—Material used Cement

Well sealed from land surface to 30 ft.

Diameter of well bore to bottom of seal 10 in.

Diameter of well bore below seal 9 in.

Number of sacks of cement used in well seal sacks

Number of sacks of bentonite used in well seal sacks

Brand name of bentonite

Number of pounds of bentonite per 100 gallons

of water lbs./100 gals.

Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Lake Driller's well number
NE 1/4 SW 1/4 Section 24 T. 41 R. 20 W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 20 ft.

Static level 20 ft. below land surface. Date 11-24-78

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 135 ft. Depth of completed well 135 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil Sandy	0	1	
Sandy gravel	1	3	
Brown Clay & gravel	3	12	
Brown Clay	12	20	
gravel WB	20	23	20
Blue clay	23	27	
Brown clay & gravel	27	84	20
Brown clay	84	108	
gravel WB	108	115	20
Blue clay & gravel	115	121	
gravel	121	135	20

Work started 11-22 1978 Completed 11-24 1978

Date well drilling machine moved off of well 11-24 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Stephen R. Wagner Date 12-16, 1978
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1171

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Sevey Well Drilling
(Person, firm or corporation) (Type or print)

Address 117 N. K. L. K. OR

[Signed] Glen L. Sevey
(Water Well Contractor)

Contractor's License No. 617 Date 12-16, 1978