NOTICE TO WATER WELL CONTRACTOR CEIN GATTER WE	RECEIVE DO JOLOG	3017	17.1
filed with the $1116 - 1071$		39/20	-16b
STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the StIATE ENGINIZER of well completion	be or lotant) ENC IN EER		
of well completion. SALEM. OR 12001	G 5643	0	
	<u> </u>		
(1) OWNER :	(11) LOCATION OF WELL:		
Name Town of Lakeview	County Lake Driller's well nu	umber	
Address 525 N. 1st St. Lakeview, OR 97630	5W 14 NW 14 Section 16 T. 37	SR. 20E	W. M
Address 52.5 No. 18t Dropharovice, OK 57050	Bearing and distance from section or subdivisio		
(2) TYPE OF WORK (check):	Block 270, 0.V.L. additio		
New Well 🔀 Deepening 🗌 Reconditioning 🔲 Abandon 🗌	Lakeview.		
If abandonment, describe material and procedure in Item 12.	One mile west of Lakeview	. Oregon	· .
(3) TYPE OF WELL: (4) PROPOSED USE (check):			\
Rotary 🕅 Driven 🗌 Domestic 🗆 Industrial 🗌 Municipal 🖾	(12) WELL LOG: Diameter of well		`
CableJettedBonesiteIndustrialIndustr	Depth drilled 360 ft. Depth of compl	eted well 360	
	Formation: Describe color, texture, grain size		
CASING INSTALLED: Threaded D Welded	and show thickness and nature of each stratu with at least one entry for each change of form		
12 " Diam. from 0 ft. to 360 ft. Gage 250	in position of Static Water Level as drilling pro	ceeds. Note drill	ing rates
" Diam. from ft. to ft. Gage	MATERIAL	From To	SWL
" Diam, from ft. to ft. Gage	soil zone, adobe, black	0 4	
PERFORATIONS: Perforated? E Yes D No.	gravel & clay, brown	4 18	
Type of perforator used factory louver perforation	a material and a grant black	18 65	ļ
7.	clay & gravel, blue	65 100	<u> </u>
	gravel, med.	100 108	
6480 perforations from 160 ft. to 340 ft.	sand, fine, blue	108 162	
perforations from ft. to ft.	clay & gravel, blue	162 302	
	cemented gravel w/void		ļ
	areas	302 318	ļ., ·
perforations from ft. to ft.	volcanic gravel, fine,		
(7) SCREENS: Well screen installed? Yes X No	gray to green	318 345	l
Manufacturer's Name	clay & gravel, black	345 360	15
Type			+
Diam. Slot size		<u> </u>	+
Diam. Slot size		<u> </u>	<u> </u>
		<u> </u>	
(8) WATER LEVEL: Completed well.		┨────┤─────	
sectic level 15 ft. below land surface Date 7/1/71	· · · · · · · · · · · · · · · · · · ·	<u> </u>	·
sian pressure lbs. per square inch Date		<u> </u>	-
(9) WELL TESTS: Drawdown is amount water level is lowered below static level			· · · · · · · ·
(9) WELL IESIS: lowered below static level			
Was a pump test made 2 Yes D No If yes, by whom driller	Work started 5/15 19 71 Complete	red 7/1	1971
d: 800 gal./min. with 75 ft. drawdown after 97 hrs.		~~ / <u>L</u>	
· · · · · · · · · · · · · · · · · · ·	Date well drilling machine moved off of well	7/3	19_7
· · · · · · · · · · · · · · · · · · ·	Drilling Machine Operator's Certification:		
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my d		
	rials used and information reported above knowledge and belief.		-
Artesian flow g.p.m. Date	[Signed] Jock Stocksberry]	Data 7/3	1071
Temperature of water 58 Was a chemical analysis made? XYes I No	(Drilling Machine Operator)	Jaw	, 13%.4
(10) CONSTRUCTION:	Drilling Machine Operator's License No.		
Well seal-Material used <u>Cement</u> pipe			
Depth of seal Cemented 80' using 24" conductor.	Water Well Contractor's Certification:		
Diameter of well bore to bottom of seal	This well was drilled under my jurisd	iction and this	report i
Were any loose strata cemented off? [] Yes [XNo Depth	true to the best of my knowledge and beli		
Was a drive shoe used? I Yes To Nobottom of Casing	NAME Jack Stooksberry.	(Type or print	;)
Did any strata contain unusable water? [] Yes X No Welded shu			
Type of water? depth of strata	Address Rt. 2, Bx. 47, Lake	EXTEM® OK	7/03
	D At P.R.	- 0	
Method of sealing strate off			
Method of sealing strata off	[Signed] ach to ohaber (Water Well Contra	ctor	
Method of sealing strata off Was well gravel packed? XYes Do Size of gravel: 3/8 Gravel placed from 80 ft. to 360 ft.	[Signed] (Water Well Contra Contractor's License No. 211. Date		