

NOTICE TO WATER WELL CONTRACTOR
 The original and first copy
 of this report are to be
 filed with the

WATER WELL REPORT

STATE OF OREGON
 (Please type or print)

RECEIVED

STATE ENGINEER, SALEM, OREGON 97310
 within 30 days from the date
 of well completion.

Lake 341

(Do not write above this line)

JUN 23 1976

State Well No.
 State Permit No. 265/14E-13

(1) OWNER:

Name Ken Kruse
 Address Fort Rock, Oregon 97735

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
 If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Casing
 Driven Jetted
 Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
 Irrigation Test Well Other

(5) CASING INSTALLED:

14 " Diam. from 2 ft. to 108 ft. Threaded Welded
 Gage 250
 " Diam. from ft. to ft. Gage
 " Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used
 Size of perforations in. by in.
 perforations from ft. to ft.
 perforations from ft. to ft.
 perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
 Type Model No.
 Diam. Slot size Set from ft. to ft.
 Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
 : gal./min. with ft. drawdown after hrs.
 " " " " " " " " " " " "
 " Blowing 1200 GPM " " "
 Bailer test gal./min. with 30 ft. drawdown after 1 hrs.
 an flow g.p.m.
 perature of water 54 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used cement
 Well sealed from land surface to 18 ft.
 Diameter of well bore to bottom of seal 18 in.
 Diameter of well bore below seal 18 in.
 Number of sacks of cement used in well seal 16 sacks
 Number of sacks of bentonite used in well seal 0 sacks
 Brand name of bentonite
 Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
 Was a drive shoe used? Yes No Plugs Size: location ft.
 Did any strata contain unusable water? Yes No
 Type of water? depth of strata
 Method of sealing strata off
 Was well gravel packed? Yes No Size of gravel:
 Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Lake Driller's well number
 NW 1/4 SE 1/4 Section 13 T. 26S R. 14E W.M.

Bearing and distance from section or subdivision corner
1340' N & 1340' W of SE corner Sec 13

(11) WATER LEVEL: Completed well.

Depth at which water was first found 18 ft.
 Static level 13 ft. below land surface. Date 5/23/76
 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8
 Depth drilled 210 ft. Depth of completed well 210 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
brn sandy soil	0	1	
tan clay	1	18	
blk sand (WB)	18	35	
green clay	35	41	
blk sand (WB)	41	55	
green clay	55	68	
blk sand & green clay (WB)	68	81	
brn sandstone	81	108	
gray rock (WB)	108	181	
brkn gray rock (WB)	181	191	
green clay & pumice (WB)	191	210	13

Work started 5/13 1976 Completed 5/23 1976
 Date well drilling machine moved off of well 5/23 1976

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] H. Williams Date 6/15, 1976
 (Drilling Machine Operator)

Drilling Machine Operator's License No. 864

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Crawford Well Drilling
 (Person, firm or corporation) (Type or print)

Address 3626 NW Coyner Redmond, Ore

[Signed] John V. Johnson
 (Water Well Contractor)

Contractor's License No. 595 Date 6/15 1976