NOTICE TO WATER WELL CONTRACTOR The original and first copy of this open.	LL REPORT		,		
water resources department SEP 7 1978 STATE OF SALEM, OREGON 97310 within 30 days from the date TER RESOURCES DEPT of well completion. SALEM. OREGON	OREGON O LO State Well No		•		
(1) OWNER:	(10) LOCATION OF WELL:				
Name Theodore Tight	County Lake Driller's well number 3				
Address Star Route	14 N. W. 14 Section 22 T. 26 S		F	W.M.	
Fort Rock, Oregon	Bearing and distance from section or subdiv		r		
(2) TYPE OF WORK (check):					
New Well ☑ Deepening □ Reconditioning □ Abandon □					
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 6/ ft.				
Rotary Driven Domestic Industrial Municipal	Static level 19 ft. below land surface. Date 8-11-78				
Dug ☐ Bored ☐ Irrigation ☑ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date				
CASING INSTALLED: Threaded □ Welded □ 4.50 "Diam. from t to 104 ft. Gage 2.50 "Diam. from ft. to ft. Gage ft	(12) WELL LOG: Diameter of well Depth drilled 262 ft. Depth of com	pleted wel	1 26	materials:	
PERFORATIONS: Perforated? Yes Proposition of the	and show thickness and nature of each stra with at least one entry for each change of form position of Static Water Level and indicate pr	nation. Rep	ort each	change in	
Type of perforator used	MATERIAL	From	То	swL	
Size of perforations in. by in.	Sandy Soil Brown	0	3		
perforations from ft. to ft.	Clay Brown	3	61		
perforations from ft. to ft.	Sand Brown	61	67	WB	
perforations from ft. to ft.	Clay Brown	67	98		
(7) SCREENS: Well screen installed? Yes WNo	Pumic Green+ White Basalt Hard Grev	198	104	WB	
Manufacturer's Name	Lava Cinders Brown	104	141	<u>w. B.</u>	
Type Model No	with Clay Streaks	141	262	W.B.	
Diam. Slot size					
Diam. Slot size Set from ft. to ft.					
(8) WELL TESTS: Drawdown is amount water level is lowered below static level					
Was a pump test made? Yes No If yes, by whom?					
Yield: gal./min. with ft. drawdown after hrs.	12" hale Come 10HIL	/			
n n	8" hole from 122' to	262'			
Air "	- Figre Trom 788 70	762			
hatter test ///O gal./min. with 18ft. drawdown after 4 hrs.					
Artesian flow g.p.m.					
perature of water Depth artesian flow encountered ft.	Work started 8-7 19 18 Comple	eted 8	-11	1978	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	8-	//	19 78	
Well seal—Material used Cement Grout Well sealed from land surface to 21 ft. Diameter of well bore to bottom of seal 18 in.	Drilling Machine Operator's Certification This well was constructed under my Materials used and information reported	v direct	super are true	vision. to my	
Diameter of well bore to bottom of sealin. Diameter of well bore below sealin.	best knowledge and belief	. Date	8-17	78	
Number of sacks of cement used in well seal67sacks	(Drilling Machine Operator)	0.		., 19	
How was cement grout placed? Gravity	Drilling Machine Operator's License No.	86	O	·	
*	Water Well Contractor's Certification:				
The second secon	This well was drilled under my jurisdiction and this report is				
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief. Name West Coast Drilling Co.				
Did any strata contain unusable water? Yes Two	(Person, firm or corporation)	(Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address 220 Academy St., Mt. Angel, OR 97362				
Method of sealing strata off	[Signed] halls 2	alle	<u></u>	**********	
Was well gravel packed? Yes No Size of gravel:	(Water Well Con		.10	٠	
Gravel placed from ft. to ft.	Contractor's License No. 519 Date	0 -	17	19 <i>78</i>	