filed with the	OREGON MAY - 01977 State Well No.	265//	15E-7	22
STATE ENGINEER, SALEM, OREGON 973.0 (Please type within 30 days from the date of well completion.	or print) ove this farter RESOURCES DEPT. SALEM. OREGON	0		••••••
(1) OWNER: LES. E. STADELI	(10) LOCATION OF WELL: County LAKE Driller's well no	ımber		•
105-12 MARCHENDO FISH VERTOYAL			E	W.M.
Address /25/3 /M/SC/[E/].NU, ILE SILVENIO	·			***************************************
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	on corner		
New Well Deepening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft			
Rotary Driven Domestic Dindustrial Municipal Cable Domestic Dindustrial Municipal	Static level 25 ft. below land surface. Date 4-20,			
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per squar	e inch. I	Date	
CASING INSTALLED: Threaded Welded Z	(12) WELL LOG: Diameter of well below casing 12 " Depth drilled ft. Depth of completed well ft.			
	Formation: Describe color, texture, grain size a and show thickness and nature of each stratu			
	with at least one entry for each change of format	tion. Repo	ort each (change ir
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	1	1	
1/pe of perforator used 70RCh	MATERIAL DOAL	From	To	SWL
Size of perforations in. by in.	TOP SOIL BRN.	0	-2	-
50 perforations from 50 ft. to 120 ft.	CLAY BRN, & GAEY	40	40 230	-
perforations from ft. to ft.			234	N.B
perforations from ft. to ft.	MES NOTA MAIS WAY SIL	30	991	<i>(6.6</i>)
(7) SCREENS: Well screen installed? Yes No	CLAY BLUE & GREY. CUBY	234	620	
Manufacturer's Name	PUMICE GREY	620	643	W.B.
Diam. Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.	CLAY BLUET GREY	443	741	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	CINDERS RED& BLK	741	774	N.E
Was a pump test made? MYes \(\subseteq No \) If yes, by whom? ORILLER				
Yield: 1080 gal./min. with 100 ft. drawdown after 3 hrs.	HARD ROCK, BASALT			
Burian water to a man	TURNING TO ANDECITE	774	800	ļ
" " " " " " " " " " " " " " " " " " "		├ ──		<u> </u>
		┼		
Bailer test gal./min. with ft. drawdown after hrs.		 		
Artesian flow g.p.m.	11	- // '	7.	7
perature of water Depth artesian flow encountered ft.	Work started 2./ 19 71 Complet		30 20	19 7
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4-0		19 7
Well seal-Material used CEMENT	Drilling Machine Operator's Certification			
Well sealed from land surface to	This well was constructed under my Materials used and information reported			
Diameter of well bore to bottom of seal in.	best knowledge and belief	7		
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date 4		, 19.7.
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	81	4	
Number of sacks of bentonite used in well seal sacks	Diffing Machine Operator & Electric 140.			
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisd	liction ar	nd this	report i
of water lbs./100 gals.	true to the best of my knowledge and be	elief.		
Was a drive shoe used? 🖺 Yes 🗆 No Plugs Size: location ft.	Name (Person, firm or corporation)		ype or pr	int)
Did any strata contain unusable water?	Address 12513 MASCHER RI	/l -	5.	-
Type of water? depth of strata	Ohisho Si	talel	<u>/</u>	
Method of sealing strata off	[Signed] (Water Well Conf	tractor)	·····	
Was well gravel packed? Yes No Size of gravel:	Contractor's License No. 5/9 Date	4.22		10"7"
Gravel placed from ft. to ft.	I TOUR SECURE AND		***********	,

₹,