

NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date
of well completion.

RECEIVED
STATE OF OREGON
(Please type or print)

JUN - 8 1977

(Do not write above this line)

State Well No. 265/16E-286

State Permit No.

(1) OWNER:

WATER RESOURCES DEPT.
Name Don Gallogly SALEM, OREGON
Address Rt 2 Box 374 Sweet Home, Ore 97236

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☒

14" Diam. from + 1 1/2 ft. to 98 1/2 ft. Gage .250
12" Diam. from 28 ft. to 48 ft. Gage .188
10" Diam. from 48 ft. to 308 ft. Gage .188

PERFORATIONS:

Perforated? ☒ Yes ☐ No.

Type of perforator used machine

Size of perforations 1/8 in. by 3 in.
8,892 perforations from 38 ft. to 308 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" blowing 1200 GPM " "

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used cement

Well sealed from land surface to 27 ft.

Diameter of well bore to bottom of seal 18 in.

Diameter of well bore below seal 18 in.

Number of sacks of cement used in well seal 27 sacks

Number of sacks of bentonite used in well seal 0 sacks

Brand name of bentonite

Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Lake Driller's well number
1/4 NW 1/4 Section 28 T. 26S R. 16E W.M.

Bearing and distance from section or subdivision corner

1400' E & 1400' S of NW corner Sec 28

(11) WATER LEVEL: Completed well.

Depth at which water was first found 22 ft.

Static level 18 ft. below land surface. Date

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 10

Depth drilled 372 ft. Depth of completed well 372 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
brn sandy soil	0	3	
diatomaceous earth	3	17	
blk sand	17	22	
green clay congl (WB)	22	106	
fine blk sand	106	153	
fine to med blk sand congl	153	308	
fine gravel-cinders-soft	308	347	
white rock (WB)			
tan clay & gravel congl (WB)	347	372	18

Work started 3/17 19 77 Completed 5/18 19 77

Date well drilling machine moved off of well 5/18 19 77

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Tim E. Lalachun Date 5/27, 1977
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1088

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Crawford Well Drilling
(Person, firm or corporation) (Type or print)

Address 3626 NW Coyner Redmond, Ore

[Signed] (Water Well Contractor)

Contractor's License No. 595 Date 5/27, 1977