NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT CEIVED

STATE OF OREGON JUN 1 3 1975 State Well No. 265/15E-33q

(Please type or print) STATE ENGINEER State Permit No. (Do not write above this line) LEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name O.R. Heavilin (Merritt Parks)	County Lake Driller's well number
Address Fort Rock, Oregon	14 NE 14 Section 33 T. 26g R. 15E W.M.
- Company - Comp	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	1320! West & 1320! South of NE corner
New Well Deepening Reconditioning Abandon	Sec 33
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Potomy IV Dulyon I	Depth at which water was first found ft.
Cable	Static level 22 ft, below land surface. Date 5/16/75
Dug ☐ Bored ☐ Irrigation 🛣 Test Well ☐ Other ☐	Artesian pressure Ibs. per square inch. Date
(3) CASING INSTALLED: Threaded Welded	400
" Diam. fromft. toft. Gage	(12) WELL LOG: Diameter of well below casing12
" Diam. fromft. toft. Gage	Depth drilled 300 ft. Depth of completed well 300 ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	Transpara
Size of perforations in. by in.	
perforations from ft. to ft.	4
perforations from ft. to ft.	
	Chart of an Con of
perforations fromft. toft.	gray clay Congl (water) 287 300 22
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	
Manufacturer's Name	
Type Model No.	
Diam Slot size ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	
Yield: gal./min. withft_drawdown after hrs.	4
"	
Bailer test 40 Fallmin with 0 ft drawdown after 1 has	
gan, man V 12 drawdown after 118.	The second secon
Artesian flow g.p.m.	
perature of water 57 Depth artesian flow encountered ft.	Work started 5/ \$5 1975 Completed 5/16 1975
(9) CONSTRUCTION:	70
•	
Well seal-Material used grout undistrubed	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	l Desi, knowledge and helief
Diameter of well bore below sealin.	[Signed] W. D. William Date 6/6/, 1975.
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No864
Number of sacks of bentonite used in well seal sacks	Diffing Machine Operator's License No
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of water	This well was drilled under my jurisdiction and this report is
of waterlbs./100 gals. Was a drive shoe used? Yes No Plugs Size: location ft.	title to the pest of my knowledge and belief.
	Name Crawford Well Drilling
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 3626 N.W. Coyner Redmond, Ore
Method of sealing strata off	[Signed] Johnson
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's Licens 25 Date6/6/, 19.75
	EETS IF NECESCADA