## RECEIVED

## STATE OF OREGON

## WATER WELL REPORT

JUN 3-1987

PLEASE TYPE or PRINT IN INI

Lake 484)

Leep-

(as required by Ords Source) PLEASE 11PE (	(for official use only)
WATEH RESOURCES DEPT.	(10) LOCATION OF WELL by legal description:
1) OWNER: SALEM, OREGON	
Name The Poplars Ranch	County LAKE CENTER & LO 4 of Section 33 of
Address ST. KT.	Township (Township is North or South), Range (Range is East or West), WM.
City Silver Lake 97038 State Open	Tax Lot Lot Block Subdivision
2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address)
lew Well □ Deepening ► Reconditioning □ Abandon □	ST. RT. SILVER LAKE ORE 97038
f abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL of COMPLETED WELL:
	Depth at which water was first found // 168 ft.
Thermal:	Static level 24" ft. below land surface. Date 5-/7-87
Rotary Mud Dug Irrigation Withdrawal Reinjection Other:	Artesian pressure lbs. per square inch. Date
Cable Bored D Piezometric Grounding Test	011
CACING INCHALLED	(12) WELL LOG: Diameter of well below casing
CASING INSTALLED: Steel  Plastic   Threaded  Welded	Depth drilled //5 ft. Depth of completed well 280 ft.
Diam. from NONE It. toft. Gauge	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of
ft. toft. Gauge	formation. Report each change in position of Static Water Level and indicate principal
	water-bearing strata.
$\begin{array}{c cccc} \textbf{LINER INSTALLED:} & \text{Steel} & \square & \text{Plastic} & \square \\ & & \text{Threaded} & \square & \text{Welded} & \square \end{array}$	MATERIAL From To SWL
Diam. from ft. to ft. Gauge	ROCK 131ACK 165 168
	ROCK BROWN & BROKEN
(6) PERFORATIONS: Perforated?  in. by in.	With Several LAYERS
*	DE BLACK ROCK 168 280
perforations from	
perforations from ft. to ft.	- F:
perforations from ft. to ft.	
7) SCREENS: Well screen installed?   Yes   No	8" Hohe to 280'
Manufacturer's Name	
Type Model No Model No.	
Diam	
Diam Slot Size	
8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Vas a pump test made? Yes \( \simega \) No If yes, by whom? ALAN PARKS	
Zield: 800 gal./min. with 2/ ft. drawdown after 2 hrs.	
, ,	
Air test gal./min. with drill stem at ft. hrs.	, page 44
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
Cemperature of water 1 2 Depth artesian flow encountered	
5) CONSTRUCTION: Special standards: Yes \( \subseteq \) No \( \subseteq \)	Date work started 5-14-87/completed 6-2-87
Well seal—Material used Seal Not Disturbed	Date well drilling machine moved off of well 5-24 1987
Vell sealed from land surface to	(unbonded) Water Well Constructor Certification (if applicable):
Diameter of well bore to bottom of seal	This well was constructed under my direct supervision. Materials used and
Diameter of well bore below seal in.	information reported above are true to my best knowledge and belief.
Amount of sealing material sacks D pounds D	[Signed] [audu [Steeks Date 6-2-37,198]
low was cement grout placed?	(bonded) Water Well Constructor Certification:
	Bond 9197438 A Issued by Fide hit A Reposit Co. of Maryla
	(number) (Surety Company Name)
Vas pump installed? Yes Type 6 THP 30 Depth 50 ft.	On behalf of CANGLE SAKINGAD  (type or print name of Water Well Constructor)
Vas a drive shoe used? ' L. Yes L. No Plugs Size: location ft.	
Did any strata contain unusable water?   Yes No	This well was drilled under my jurisdiction and this report is true to the
Type of Water? depth of strata	best of my knowledge and belief:
Method of sealing strata off	(Signed)
Vas well gravel packed? Yes No Size of gravel:	(Water Well Constructor)

Gravel placed from