STATE OF OREGON

WELL I.D. LABEL# L $_{114391}$

WATER SUPPLY WELL REPORT		± 3 4 330	CTADE CADD #	11.051		
		/2014	START CARD#		1023097	
(as required by ORS 537.765 & OAR 690-205-0210)	8/11	/2014	ORIGINAL LOG #			
1) LAND OWNER Owner Well I.D.						
T) LAND OWNER Owner Well I.D. Last Name VOTTO		(9) LOCAT	TION OF WELL (legal of	description)		
Company			Twp 39.00 S N	-	E E/W WN	
Address 93905 PIKE LN.			NW 1/4 of the NE			
City LAKEVIEW State OR Zip 97630		Tay Man Numb				
2) TYPE OF WORK New Well Deepening Con	nversion	Tax Map Numb	ber" or		DMS or DD	
Alteration (complete 2a & 10) Abandonment(complete 5a)	Lat	OI.		DMS or DD DMS or DD	
2a) PRE-ALTERATION		Long°	reet address of well	annat addusas	_ DMS of DD	
Dia + From To Gauge Stl Plstc Wld Thrd Casing:				earest address		
		93905 PIKE L	N. LAKEVIEW			
Material From To Amt sacks/lbs Seal:						
3) DRILL METHOD		(10) STATI	C WATER LEVEL			
Rotary Air Rotary Mud Cable Auger Cable Muc	1	(10) 51/111	Date	e SWL(psi) +	SWL(ft)	
	1	Existing W	Vell / Pre-Alteration		2(14)	
Reverse Rotary Other		Completed			5.9	
4) PROPOSED USE Domestic X Irrigation Communi	ty		Flowing Artesian?	Dry Hole?		
Industrial/ Commericial Livestock Dewatering	•	WATER BEAR	ING ZONES Depth w	vater was first found	14 00	
Thermal Injection Other		SWL Date	•	st Flow SWL(psi)		
			From To Es	st Flow SWL(psi)	+ SWL(II)	
	(Attach copy	7/23/2014	58 372	1500	5.85	
Depth of Completed Well 387.00 ft.						
BORE HOLE SEAL	sacks/	′				
	Amt lbs					
24 0 56 Cement 0 56	46 S					
20 56 387		1 -	-			
		(11) WELL	LOG Ground Elevation			
How was seal placed: Method A B X C D			Ground Elevation			
	E	Fine brown sar	Material	From	To 14	
Other		Pea gravel	id	14	16	
Backfill placed from ft. to ft. Material		Fine brown sar	ad	16	21	
Filter pack from ft. to387ft. Material PEA GRAV Size		Pea gravel	IU	21	24	
Explosives used: Yes Type Amount		fine brown san	d with gravel	24	50	
5a) ABANDONMENT USING UNHYDRATED BENTON		Grey clay	a will graver	50	58	
Proposed Amount Actual Amount			stone/sand/gravel/shells	58	74	
		Gravel with sar		74	82	
6) CASING/LINER Casing Liner Dia + From To Gauge Stl Plsto	Wild Thud	fractured sands	stone	82	91	
		gravel and coar	rse sand	91	130	
			actured sandstone layers	130	144	
	∮		stone with gravel	144	148	
	$\forall \vdash \vdash \vdash$	sandy grey clay	,	148	156	
	$A \vdash H$		clay stone w/ gravel	156	169	
Shoe Inside Outside Other Location of shoe(s)		sandy grey clay		169	189	
		coarse sand and		189	202	
Temp casing Yes Dia From To		sandy grey clay	stone with gravel	202	213	
Y) PERFORATIONS/SCREENS		Fractured grey		218	234	
Perforations Method Saw cut		Tractured grey	ciay stone	210	234	
Screens Type Material		Date Started	[7/22/2014 Com	nplete <u>8/6/2014</u>		
Perf/ Casing/ Screen Scrn/slot Slot # o		(unbonded) V	Vater Well Constructor Certif	fication		
Screen Liner Dia From To width length slot Perf Liner 12 247 387 .125 3 520			the work I performed on the c		ng alteration o	
Fell Line 12 247 387 .123 3 320	00		of this well is in compliance			
			tandards. Materials used and in			
			knowledge and belief.	1		
		License Numb	per 1940 E	Date 8/11/2014		
NEIL TESTS. Minimum tooting time in 1 hours			1740	0/11/2014		
3) WELL TESTS: Minimum testing time is 1 hour		Signed BEN	NJAMIN FRY (E-filed)			
	Artesian					
Yield gal/min Drawdown Drill stem/Pump depth Duration	(hr)	` ′	er Well Constructor Certifica			
1000 160 2			nsibility for the construction, of			
1500 200 1			d on this well during the constr			
			ring this time is in complian			
Temperature 56 °F Lab analysis Yes By		-	andards. This report is true to t	-	euge and belief.	
Water quality concerns? Yes (describe below) TDS amount Prom To Description Amoun	<u> </u>	License Numb	er <u>1355</u> D	Date 8/11/2014		
From To Description Amoun	t Units	G:- 1				
	+					
	+	Contact Info (c	optional)			

LAKE 52538

WELI

L I.D. LABEL# L	114391	
START CARD#	1023697	
RIGINAL LOG#		

• 0	8/11	1/2014		ORIGINAL LO	OG#			
2a) PRE-ALTERATION		Water Q	uality Cor	ncerns				
Dia + From To Gauge Stl Plstc Wld Thrd		From	То	Descrip	tion	Amo	unt	Units
Material From To Amt sacks/lbs						$-\!\!+\!\!\!-$		
THOR TO AIR SUCKS/IDS								
		(10) STA	TIC WA	TER LEVEL				
5) BORE HOLE CONSTRUCTION		SWL Date			Fst Flow	SWL(psi)	+	SWI (ft)
BORE HOLE SEAL	sacks/	511234	1101		LSt 110W	5 (FSI)	1 <u> </u>	SWE(II)
Dia From To Material From To	Amt lbs							
							$ \square$	
						<u> </u>	+	
							1	
							$ \square $	
						<u> </u>	┨	
							┧┝╅	
FILTER PACK		(11) WEI	LIOC					
From To Material Size		(11) WEI						
		G 1 31	Mate	erial		From	—	To
		Gravel with	n sand			234 242	-	242 243
		sand grey c	lay with w	ood		243		248
6) CASING/LINER		sandy grey gravel, san		gravel and wood		248 262		262 364
Casing Liner Dia + From To Gauge Stl Plstc	Wld Thrd	fractured cl		layers		364		368
		gravel with				368		372
	\vdash	grey clay				372	_	387
	HHH						_	
	HHI							
7) PERFORATIONS/SCREENS							_	
	of Tele/							
	lots pipe size							
							$ \vdash$	
						-		
		Commer	nte/Doma	rke				
		Commen	105/IXCIII	11 172				
(8) WELL TESTS: Minimum testing time is 1 hour								
	tion (hr)							