NOTICE TO WATER WELL CONTRACTOR, The original and first copy of this report are to be tate Well No. 265/162-5 STATE ENGINEER, SALEM, OREGON 97310 R 2 7 1976 STATE OF OREGON (Please type or print) tate Permit No. .. within 30 days from the date of well completion. WATER RESOURCE Do Don Write above this line) CALEM. CRECON (10) LOCATION OF WELL: (1) OWNER: county Lake Driller's well number Mika Johnson K. Dale Johnson Name NE 14 NE 14 Section 27 T. 265 R. 16E Fort Rock fore Address Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): 1317' W & 620' S of NE Corner Sec 27 Reconditioning [ New Well □x Deepening [ If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (4) PROPOSED USE (check): (3) TYPE OF WELL: Depth at which water was first found Driven 🗆 ft. below land surface. Date 4/8/76 Rotary Static level 35 Domestic | Industrial | Municipal | Jetted 🛚 Cable lbs, per square inch. Date Irrigation Test Well | Other Bored | Artesian pressure (5) CASING INSTALLED: (12) WELL LOG: Threaded | Welded | K Diameter of well below casing .....1.2..... 14. " Diam. from  $+ 1\frac{1}{2}$  ft. to  $110\frac{1}{2}$  ft. Gage . 250 ft. Depth of completed well 510 Depth drilled Formation: Describe color, texture, grain size and structure of materials; " Diam. from \_\_\_\_\_ ft. to \_\_\_\_ ft. Gage and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. (6) PERFORATIONS: Perforated? | Yes | No. MATERIAL From Type of perforator used Brn sandy soil in. by Size of perforations 30 tan sticky clay perforations from \_\_\_\_\_ ft. to \_\_\_\_ 30 46 green clav perforations from ...... ft. to ..... 53 46 green clay & blk sand (WB) perforations from \_\_\_\_\_ ft. to \_\_\_\_\_ 75 green clay (7) SCREENS: 75 Well screen installed? 

Yes 

No blk sand & tan clay (WR) 101 101 green sticky clay 📧 Manufacturer's Name ..... blk sand fine to med & 170 Diam. Slot size ..... Set from ..... pumice) (WB) 334 384 Diam. \_\_\_\_\_ ft, to \_\_\_\_\_ ft. green clay 392 (WB) <u> 384</u> blk sand med Drawdown is amount water level is lowered below static level (8) WELL TESTS: 392 510 green & tan clay Was a pump test made? Tyes No If yes, by whom? gal./min. with ft. drawdown after hrs. " Est 700 gals "blowing Bailer test 10 gal./min. with offt. drawdown after 1 esian flow g.p.m. 3/26 19 76 Completed 4/8 19 76 Temperature of water 54 Depth artesian flow encountered Work started 19 76 Date well drilling machine moved off of well (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used .\_\_\_\_ Cement This well was constructed under my direct supervision. Materials used and information reported above are true to my Well sealed from land surface to \_\_\_\_\_\_59 best knowledge and belief. Diameter of well bore to bottom of seal \_\_\_\_\_in. [Signed] W. W. Williams Date 4/24, 19.76 (Drilling Machine Operator) Number of sacks of cement used in well seal ..... Drilling Machine Operator's License No. 864 Number of sacks of bentonite used in well seal ......Q Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is lbs./100 gals. true to the best of my knowledge and belief. Was a drive shoe used? ☐ Yes ☐ No Plugs ...... Size: location ...... ft. Name Crawford Well Drilling (Type or print)
(Person, firm or corporation) (Type or print)

[Signed]

Did any strata contain unusable water? 

Yes 

No

Gravel placed from \_\_\_\_\_ ft. to \_\_\_\_

Was well gravel packed? 

Yes No Size of gravel: ...

Type of water?

Method of sealing strata off

depth of strata

Address 3626 NW Coyner Redmond, Ore

Contractor's License No. 295 Date 4/24 19.76

(Water Well Contractor)