NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

Lake 675

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 26s/18E-29ch

State Permit No.

(1) OWNER:
Name Larry Grossman
Address PO Box 240 Deer Lodge Motel, Christmas Valley Oregon 97630

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☑ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☑ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☑
4" Diam. from 0 ft. to 120 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes ☑ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☐ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer [test pit] 600 gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used cement grout
Well sealed from land surface to 120 ft.
Diameter of well bore to bottom of seal 19 in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal 43 sacks
How was cement grout placed? pressure grouted
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Lake Driller's well number 96
NW ¼ SW ¼ Section 29 T. 26S R. 18E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 156 ft.
Static level 16 ft. below land surface. Date May 5 80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 10"
Depth drilled 436 ft. Depth of completed well 435 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Brown Sand	0	3	
Diatomaceous earth	3	17	
Green Clay	17	27	
Gray Clay	27	37	
Gray clay	37	62	
Black sand w/p	62	115	16
Green Clay	115	156	
white pumus w/p	156	160	16
Green Clay	160	195	
white pumus	195	199	
dark green Clay	199	420	
Green Clay and	420	436	
small pumus seams w/p			16

Work started May 2 1980 Completed May 5 1980
Date well drilling machine moved off of well May 5 1980

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Stan L Adams (Drilling Machine Operator) Date May 7, 1980
Drilling Machine Operator's License No. 1302

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Tyle Adams (Person, firm or corporation) (Type or print)
Address RT3 Box 122 X Nibbor, Ore 97123
[Signed] Tyle Adams (Water Well Contractor)
Contractor's License No. 690 Date May 7, 1980

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119