

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No. 265/19E-5C

State Permit No. 6-9122

(1) OWNER:

Name Richard Mensch
Address P.O. Box 516
Christmas Valley, Ore. 97638

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
☐ Jetted ☐
☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☐
14" Diam. from 0 ft. to 59 ft. Gage 1250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
" (air 2500) gal./min with ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 59 ft.
Diameter of well bore to bottom of seal 10 1/4 in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal 42 sacks
How was cement grout placed? pressure grouted

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Lake Driller's well number 127
SE 1/4 SW 1/4 Section 5 T. 26S R. 19E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 94 ft.
Static level 17 ft. below land surface. Date Nov 6 80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 10"
Depth drilled 178 ft. Depth of completed well 177 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Sandy Brown clay	0	12	
Brown clay	12	26	
Green shale-med	26	84	
Black sandstone	84	87	
Gray Basalt-hard	87	93	
Broken Basalt-lava Gray	93	110	17
Gray Basalt-hard	110	130	
Layered Basalt	130	178	17
Broken lava w/B			

RECEIVED

DEC 12 1980

WATER RESOURCES DEPT
SALEM, OREGON

Work started Nov 5 19 80 Completed Nov 6 19 80
Date well drilling machine moved off of well Nov 11 19 80

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Don Adams Date Nov 11, 1980
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1302

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Tyler Adams
(Person, firm or corporation) (Type or print)

Address Box 467 Christmas Valley Ore 97638

[Signed] Tyler Adams
(Water Well Contractor)

Contractor's License No. 690 Date Nov 11, 1980