

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED

State Well No.

DEC 14 1976

State Permit No.

WATER RESOURCES DEPT.

(1) OWNER:

Name

Address

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☒

12" Diam. from +1 1/2 ft. to 35 1/2 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " " " "
" " " " " "

Bailer test 22 gal./min. with 0 ft. drawdown after 2 hrs.

Artesian flow g.p.m.

Temperature of water 44° Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Portland Cement

Well sealed from land surface to 35 1/2 ft.

Diameter of well bore to bottom of seal 16 in.

Diameter of well bore below seal 12 in.

Number of sacks of cement used in well seal 517 sacks

Number of sacks of bentonite used in well seal sacks

Brand name of bentonite

Number of pounds of bentonite per 100 gallons

of water lbs./100 gals.

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel: ft.

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County

Driller's well number

SW 1/4 NW 1/4 Section 26 T. 27S R. 13E W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 278 ft.

Static level 226 2/3 below land surface. Date 12-6-76

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 12"

Depth drilled 298 ft. Depth of completed well 298 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil, Brown	0	5	
Clay, Brown	5	45	
Sandstone, Brown	45	125	
Clay, Brown	125	140	
Brown Sandstone, clay conglomerate	140	145	
Rock, lava, Brown, Hard	145	155	
Brown Sandstone, clay conglomerate	155	240	
Black sandstone + clay conglomerate	240	260	
Clay, green	260	278	226
Sand, coarse, BIK water Brg	278	298	218
			213

Work started 10-25 1976 Completed 12-6 1976

Date well drilling machine moved off of well 12-7 1976

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Alvin Schunk Date 12-7, 1976

(Drilling Machine Operator)

Drilling Machine Operator's License No. 960

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Schunks Drilling Service

(Person, firm or corporation)

(Type or print)

Address 4911 SW Elkhorn, Redmond, Ore. 97756

[Signed] Alvin Schunk

(Water Well Contractor)

Contractor's License No. 627 Date 12-7, 1976