NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No. State Permit No. .

,	
(1) OWNER:	(10) LOCATION OF WELL:
Name Calvin LAIRD	County LAKE Driller's well number 104
Address Lithsum Rt. Box 128A	7 1 14 7 W 1/4 Section - 2 T. 275 R. 15 E W.M.
mystle Point, Dryon 97458	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Description Council
New Well	52 PNW4
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 185 ft.
Rotary Driven Domestic Dindustrial Diffusional D	
☐ Jetted ☐ Irrigation ☐ Test Well ☐ Other ☐	
	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
14	Depth drilled 36/ ft. Depth of completed well 35% ft.
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Sandy Brown Soil 0/2
perforations from ft. to ft.	Sandy Brown Clay 12 60
perforations from ft. to ft.	Green clays to 60 101
perforations from ft. to ft.	Black sandstone cong 101 190 16
(7) SCREENS: Well screen installed? Yes No	Green day 190 211
Manufacturer's Name	med hard Brown glay & shale 211 275
Type Model No.	Gray basalt have 275 253
Diam Slot size Set from ft. to ft.	Brocken brown vack 253 336 Brochen brown law wa 336 361 16
Diam. Slot size Set from ft. to ft.	15100 (Et) 57024 - CAP 7B 550 501 16
(8) WELL TESTS: Drawdown is amount water level is	
lowered below static level	R
a pump test made? Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs,	JUL 25 1980 00 T 9 4 1999
" " "	WATER RESOURCES DEPTWATER RESOURCES DE
" air Test" " "	SALEM, OREGON WATER RESOURCES DE
er test 2000 gal./min. with ft. drawdown after / hrs.	SALEM, OREGON
Artesian flow g.p.m.	
nperature of water Depth artesian flow encountered ft.	Work started May 28 19 80 Completed May 31 19 80
(9) CONSTRUCTION:	Date well drilling machine moved off of well May 3/ 19
Well seal-Material used Lement	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Stor Ladory Date Acore 10 80
Number of sacks of cement used in well seal	(Dinning Machine Operator)
How was cement grout placed?	Drilling Machine Operator's License No.
The state of the s	Water Well Contractor's Certification:
The second secon	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes M No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Tyes No	Name Oyle Racon (Person firm or correction) (Three or wind)
Type of water? depth of strata	Address 11345/122X Helpfor Print)
Method of sealing strata off	TOBA
	[Signed] Lyle Odoms
	(Water Well Contractor) Contractor's License No. 670 Date 1970
Gravel placed from	Contractor's License No. 6/0 Date 1970