NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED
JUN 28 1977
WATER RESOURCES DEPT.
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print) (Do not write above this line)

Lake 831

State Well No. 27s/15E-24cc

State Permit No.

(1) OWNER:
Name Darrell Bowen
Address Silver Lake, Or. 97638

(2) TYPE OF WORK (check):
New Well ☐ Deepening ☐ Reconditioning ☒ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

CASING INSTALLED:
Threaded ☐ Welded ☐
17 " Diam. from 0 ft. to 101 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? ☐ Yes ☒ No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 20 gal./min. with 0 ft. drawdown after 3 hrs.
Artesian flow g.p.m.
Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 101 ft.
Diameter of well bore to bottom of seal 17 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 10 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Lake Driller's well number
SW ¼ SW ¼ Section 24 T. 27S R. 15E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found N/A Repair Only ft.
Static level 28 ft. below land surface. Date 6/25/77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 8 in
Depth drilled — ft. Depth of completed well 362 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
~~Cleaned off Sand~~		Fill Only	
Reamed old hole to 17" from 0 to 101			
Brown Clay	0	38	
Sand Stone	38	59	
Blue Clay	59	101	
Cleaned off Sand Fill From 200' to Bottom off hole			

Work started 6/6 1977 Completed 6/25 1977
Date well drilling machine moved off of well 6/25 1977

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Allen B Woods Date 6/27, 1977
(Drilling Machine Operator)
Drilling Machine Operator's License No. 1015

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Blaylock & Woods Well drilling
(Person, firm or corporation) (Type or print)
Address P.O. Box 12 Silver Lake, Or.
[Signed] Silver Blaylock
(Water Well Contractor)
Contractor's License No. 425 Date 6/27, 1977

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119