NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

Lake 852

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 27s/16E-5a
State Permit No. 6-8981

(1) OWNER:
Name GERALD LADIEU
Address STAR RT. SILVER LAKE ORE. 97638

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☑ Jetted ☐
Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☑ Test Well ☐ Other ☐

(5) CASING INSTALLED:
Threaded ☐ Welded ☑
14" Diam. from 0 ft. to 101 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:
Perforated? ☐ Yes ☑ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☑ Yes ☐ No If yes, by whom? Ron Johnson
Yield: 1000 gal./min. with 67'6" ft. drawdown after 2 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 70° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used PORTLAND CEMENT
Well sealed from land surface to 30 ft.
Diameter of well bore to bottom of seal 18 in.
Diameter of well bore below seal 14 in.
Number of sacks of cement used in well seal 45 sacks
How was cement grout placed? pumped
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County LAKE Driller's well number
¼ NE ¼ Section 5 T. 27S R. 16E W.M.
Bearing and distance from section or subdivision corner
CENTER NE¼ FOR PIVOT IRRIGATION

(11) WATER LEVEL: Completed well.
Depth at which water was first found 860 ft.
Static level 19'6" ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 8"
Depth drilled 880 ft. Depth of completed well 880 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL SANDY BROWN	0	3	
DIATOMITE	3	32	
CLAY GRAY	32	860	
ROCK BROKEN BLACK	860	880	19'6"

RECEIVED
MAR 26 1980
WATER RESOURCES DEPT
SALEM, OREGON

Work started 3-10 1980 Completed 3-20 1980
Date well drilling machine moved off of well 3-20 1980

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Ronald Johnson Date 3-24, 1980
(Drilling Machine Operator)
Drilling Machine Operator's License No. 1003

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Claude BLACKMAN
(Person, firm or corporation) (Type or print)
Address P.O. Box 100 XMAS Valley Ore. 97638
[Signed] Claude Blackman
(Water Well Contractor)
Contractor's License No. 657 Date 3-24, 1980

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119