

WATER WELL REPORT

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

STATE OF OREGON
(Please type or print)

(Do not write above this line)

State Well No. 25S/13E-279C
State Permit No. 6-9071
WELL # 7

(1) OWNER:

Name Wagner Farms
Address Ray Wagner St Rt Ft Rock

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Drilled ☒ Jetted ☐
Bored ☐ Dug ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☒
4" Diam. from 0 ft. to 169 ft. Gage 25 & 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " "

" " " "

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used cement
Well sealed from land surface to 28 ft.
Diameter of well bore to bottom of seal 16 1/4 in.
Diameter of well bore below seal 12" to 210 10" ↓
Number of sacks of cement used in well seal 26 sacks
How was cement grout placed? pressure grouted

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Lake Driller's well number 109
SW 1/4 NE 1/4 Section 27 T. 25 R. 13E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 180 ft.
Static level 122 ft. below land surface. Date June 25
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 12" - 10"

Depth drilled 286 ft. Depth of completed well 266 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Sandy brown soil	0	4	
Sand & gravel cong	4	20	
brown gray lava ind soft	20	46	
Broken gravel gray lava	46	136	
Sandstone brown med	136	145	
broken gray basalt	145	160	
gray gravel coarse	160	164	
Gray lava rock med	164	180	
W/B gray gravel	180	193	
Gray brown lava med	193	286	
Small gravel seams			122

RECEIVED

JUL 2 1980

WATER RESOURCES DEPT
SALEM, OREGON

Work started June 25 1980 Completed June 25 1980
Date well drilling machine moved off of well June 26 1980

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Sten J Adams Date June 26 1980
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1302

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name J. Adams
(Person, firm or corporation) (Type or print)

Address PO Box 467 C V

[Signed] J. Adams
(Water Well Contractor)

Contractor's License No. 190 Date June 26, 1980