NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date

WATER WELL REPORT

STATE OF OREGON

(Please type or print

State Well No. 275/1

SP*45656-119

of well completion. (Do not write a	bove this line) State Permit No. 977110 Section 1
(1) OWNER:	(10) LOÇATION OF WELL:
Name Chick notinger	County Lake Driller's well number 102
Address 10 Cox 1213 Ochrishmas Valley Ore	56 47 W 4 Section 8 T. 27 S R. 17 E W.M.
97638	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Bearing and distance from Section of Subdivision corner
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 700 ft.
Rotary Driven Domestic Industrial Municipal D	
D Jetted Donnestre Industrial Industri	
	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 18"
## "Diam from 0 ft to 102 ft. Gage 1375	Depth drilled \$5 % ft. Depth of completed well \$5 % ft.
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated.
(6) PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in by in.	Sandy Soil Brown 0 2
perforations from ft. to ft.	Diatomations parts 2 12
perforations from ft. to ft.	Brown Clay 12 28
perforations from ft. to ft.	Orzen Clay 26 89
(7) SCREENS: Well screen installed? [] Yes El Vo	Gray Clay 59 80
West Bottom Misselfett, [] Yes ag 140	Green clay 80 315
Manufacturer's NameModel No	White Aumus gravel 398 405
Diam. Slot size Set from ft. to ft.	6 repr Clay 905 698
Diam. Slot size Set from ft. to ft.	Black sand
	Reck Sand W/R 705 788
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Gray Busalt 788 192
a pump test made? Yes WNo If yes, by whom?	YELFIVEN
Yield: gal./min. with ft. drawdown after hrs.	
" " " " " " " " " " " " " " " " " " "	idAY 2 0 1986
" / " " " " "	WATER RESOURCES DEET
test 1800 gal./min. with ft. drawdown after / hrs.	SOURCES DEPT
lesian flow g.p.m.	SALEM. OREGON
Temperature of water Depth artesian flow encountered ft.	Work started May 24 1980 Completed May 24 1980
(9) CONSTRUCTION:	Date well drilling machine moved off of well Hory 26 1980
Well seal—Material used Cerro	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in. in.	best knowledge and belief.
Diameter of well bore below sealin.	[Signed] . Sten I Adoma Date Way 26, 1950
Number of sacks of cement used in well seal	Drilling Machine Operator) Drilling Machine Operator's License No
How was cement grout placed?	Drining Machine Operator's License No
	Water Well Contractor's Certification:
A STATE OF THE STA	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Tyes Two Plugs Size: locationft.	true to the best of my knowledge and belief. Name Like Characterists
Did any strata contain unusable water? TYes No	(Type or print)
Type of water? depth of strata	Address 193 Box 122 X Willshood 19, 97/23
Method of sealing strata off	2100
Was well gravel packed? [] Yes [] No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 690 Date 7 26 1980
(USE ADDITIONAL SH	
· · · · · · · · · · · · · · · · · · ·	LETS IF NECESSARY) (SP*45656-119