

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

RECEIVED WATER WELL REPORT

JUL 16 1980

STATE OF OREGON
(Please type or print)

WATER RESOURCES DEPT
SALEM, OREGON

State Well No.

State Permit No. 6-9071

WELL # 3

(1) OWNER:

Name Wagner FARMS
Address RAY WAGNER
1400 N. 1st St. Rock, Oregon 97735

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Jettied ☐
Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☒
14" Diam. from 0 ft. to 166 ft. Gage 375
" Diam. from " ft. to " ft. Gage
" Diam. from " ft. to " ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from " ft. to " ft.
perforations from " ft. to " ft.
perforations from " ft. to " ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from " ft. to " ft.
Diam. Slot size Set from " ft. to " ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Test 1000 gal./min. with ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 166 ft.
Diameter of well bore to bottom of seal 16 1/4 in.
Diameter of well bore below seal 10 in. 78
Number of sacks of cement used in well seal sacks
How was cement grout placed? pressure grouted

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from " ft. to " ft.

(10) LOCATION OF WELL:

County Lake Driller's well number 107
SW 1/4 SE 1/4 Section 27 T. 25S R. 13E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 306 ft.
Static level 122 ft. below land surface. Date June 12
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 10"
Depth drilled 324 ft. Depth of completed well 320 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Sandy brown soil	0	1	
brown clay & med gravel	1	8	
brown sandstone	8	68	
brown sandstone & shale	68	81	
red-brown lava - broken	81	158	
brown-red basalt	158	171	
brown clay	171	202	
brown basalt - hard	202	209	
brown sandstone & boulders	209	250	
Gray basalt - hard	250	306	
red porous broken lava	306	322	
w/b Gray basalt - hard	322	324	122

Work started June 9 19 80 Completed June 12 19 80
Date well drilling machine moved off of well June 12 19 80

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Tyle Adams Date June 15, 1980
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1292

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Tyle Adams (Type or print)
(Person, firm or corporation)

Address Box 122 X Hillsboro, OR 97123

[Signed] Tyle Adams (Water Well Contractor)

Contractor's License No. 690 Date June 15, 19 80