NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97510 within 30 days from the date of well completion.

WATER WELL REPORT CEIVED

STATE OF OREGON MAY 1 4 1975 State Well No. 1999 3w - 7

(Please type or print) STATE ENGINEERState Permit No. LANE 11038

(Do not write above this line) SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Halland Farms Inc.	County Lane Driller's well number
Address R# 2 Box 299-B	55 1/4 5 51/4 Section 9 T. 175 R. 3 W W.M.
Eugene Oregon	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	9
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found / ft.
Rotary Driven Domestic Dindustrial Municipal Domestic Municipal Domestic	Static level /8 ft. below land surface. Date 4/11/75
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below ageing 20'
12 " Diam. from 7 2 ft. to 260 ft. Gage 250	Diameter of well below casing
"Diam. fromft, toft, Gage	Depth drilled 260 ft. Depth of completed well 260 ft.
ft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes 🗆 No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Sandy Loan 08
1000 perforations from 20 ft. to 800 ft.	50nd/4 nav = 18 18
1700 perforations from 100 ft. to 260 ft.	Cerment grove 18 25
perforations from ft. to ft.	Sand gravel
	Chy Brown 25
(7) SCREENS: Twell/screen installed? The I No	ALAB TGrave 15/14 80
Manufacturer's Name Johns O	ah.
Type 1 1 90 0 Model No.	Sand Topravel 80 100
Diam. S. Slot size Set from 11. to 11.	
Diam. Slot size Set from ft. to ft.	Sand grave Cdy 100
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	with woler streeks 200 to
Was a pump test made? It is I No If yes, by whom? Priller	
Yield: 630 gal./min. with 60 ft. drawdown after 5 hrs.	
n y y y	10 10 10 10 10 10 10 10 10 10 10 10 10 1
n n n n n n n n n	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 1975 Completed 41/5 1975
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4 1975
Well seal-Material used Coament Slarry	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and relief.
Diameter of well bore below seal in.	[Signed] Signed Date The 1925
Number of sacks of cement used in well seal sacks	(Drilling Mathine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.
Brand name of bentonite	77 1 0 1 0 1 0 1 0 1 1 0 1 1 1 1 1 1 1 1
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? 🗆 Yes 🛂 No Plugs Size: location ft.	
Did any strata contain unusable water?   Yes   You	Name (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 27 20 // \din 5 // d
Method of sealing strata off	[Signed] Frank Wilson
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from 20 ft. to 260 ft.	Contractor's License No. 5.62 Date 7/23, 19.75