

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

RECEIVED STATE OF OREGON STATE ENGINEER SALEM, OREGION OCT 13 1967 (Please type or print) (Do not write above this line) RECEIVED STATE OF OREGON STATE ENGINEER SALEM, OREGION OCT 26 1967

State Well No. 17/34w-18badca State Permit No. LANE 11224

Industrial - 7-3-67

(1) OWNER:

Name Eugene Sand & Gravel Address P. O. Box 1067, Eugene, Oregon

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [X] Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:

16" Diam. from plus 18" ft. to 131'6" ft. Threaded [] Welded [] Gage .250

(6) PERFORATIONS:

Type of perforator used Mills Knife Size of perforations 3/8 in. by 3 in. perforations from 1000 ft. to 131'6" ft. to 18 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 13 ft. below land surface Date 7/27/67

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [X] Yes [] No If yes, by whom? Ramsey Waiter Yield: 600 gal./min. with 41 ft. drawdown after 19 hrs.

(10) CONSTRUCTION:

Well seal—Material used Bentonite Depth of seal 18 ft. Diameter of well bore to bottom of seal 19 in. Were any loose strata cemented off? [] Yes [X] No Depth Was a drive shoe used? [X] Yes [] No Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Lane Driller's well number 1/4 Section 18 T. 17S R. 3W W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 16" Depth drilled 133 ft. Depth of completed well 132 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Soil, Sand & Gravel Tight, Sand & Gravel, Sand & Gravel W/Clay, Sand & Gravel W/Clay loose, Sand & Gravel w/clay - clay, Sand w/clay - small gravel, Sand & Gravel w/clay, Sand w/clay, Sand & Gravels w/clay, Sand & Gravels w/clay - clay, Large Gravels w/cemented sand and clay, Basalt.

Work started 7-6-1967 Completed 7-27 19 67 Date well drilling machine moved off of well 7-27 19 67

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Carl G. [Signature] Date 10-12, 1967 (Drilling Machine Operator)

Drilling Machine Operator's License No. 386

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Christensen Drilling & Irrigation (Person, firm or corporation) (Type or print)

Address 3550 West 18th, Eugene, Oregon

[Signed] Mark W. Christensen (Water Well Contractor)

Contractor's License No. 97 Date 8-5, 19 67