

WATER WELL REPORT

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

RECEIVED

STATE OF OREGON
(Please type or print)

JUN 10 1977

(Do not write above this line)

State Well No. 175/lew-1

State Permit No.

(1) OWNER: WATER RESOURCES DEPT.

Name GORDAN I KADAMMER, & BOOTH
Address 2060 Dewey St
Eugene, Oregon

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:

6" Diam. from +1 ft. to 25 ft. Gage 250 W
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations	in. by	in.
perforations from ft. to ft.		
perforations from ft. to ft.		
perforations from ft. to ft.		

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☒ Yes ☐ No If yes, by whom? Driller

Yield: 8 gal./min. with 70 ft. drawdown after 4 hrs.

Bailer test 15 gal./min. with 20 ft. drawdown after 1 hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used CEMENT
Well sealed from land surface to 25 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 8 sacks
How was cement grout placed? filled 10 hole & churned in to surface level &

Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Lane Driller's well number
1/4 1/4 Section 1 T. 17-N R. 6-W W.M.

Bearing and distance from section or subdivision corner

Platt 1110

(11) WATER LEVEL: Completed well.

Depth at which water was first found 205 ft.

Static level 30 ft. below land surface. Date 6/8/77

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6 inch

Depth drilled 300 ft. Depth of completed well 300 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Orange Sandy Clay	0	15	RTX
Brown Sand Stone	15	20	11
Blue Tuff Sand Stone	20	300	11

Work started 5/87 1977 Completed 6/8 1977

Date well drilling machine moved off of well 6/9 1977

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Barclay Date 6/9, 1977
(Drilling Machine Operator)

Drilling Machine Operator's License No. 512

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name C.E. GORDINIER & SON
(Person, firm or corporation) (Type or print)

Address 1941 HARRIS ST Eugene, Oregon

[Signed] Clayton E. Gordinier
(Water Well Contractor)

Contractor's License No. 395 Date 6/9, 1977