

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

RECEIVED
MAY 11 1966

STATE OF OREGON (Please type or print)

Job # 68

STATE ENGINEER, SALEM, OREGON

G-3630

State Well No. 17/400-3B
State-Permit No. LANE 11707

(1) OWNER: Gordon Elliott
 Name: Gordon Elliott
 Address: 1287 Irvington Avenue, Eugene, Oregon

(2) LOCATION OF WELL:
 County: Lane Driller's well number: 4W.W.M.
 1/4 Section 3 T. #175R.
 Bearing and distance from section or subdivision corner: 3101'E & 400'S of NW corner, Well #2, Sec. 3

(11) WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom? 406

Yield: 556 gal./min. with 140 ft. drawdown after 112 hrs.

Baller test gal./min. with ft. drawdown after hrs.
 Artesian flow g.p.m. Date
 Temperature of water Was a chemical analysis made? Yes No

(3) TYPE OF WORK (check):
 New Well Deepening Reconditioning Abandon
 Abandonment, describe material and procedure in Item 12.

(12) WELL LOG: Diameter of well below casing 10"
 Depth drilled 220 ft. Depth of completed well 220 ft.
 Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

(4) PROPOSED USE (check):
 Domestic Industrial Municipal Irrigation Test Well Other
 Rotary Cable Dug Driven Jetted Bored

MATERIAL	FROM	TO
silt + med. gravel	0	9
clay + gravel	9	30
med. gravel (loose) w	30	36
gravel + clay	36	56
large & med. gravel (loose)	56	81
med. gravel & clay cemented	81	94
sand & br. clay (cemented)	94	101
sand (med.) + water	101	103
gravel + clay	103	173
S. gravel - sand - clay	173	194
S. gravel - sand (w)	194	196
med. & S. gravel - sand (w)	196	212
blue clay & gravel	212	213
blue clay	213	220

(6) CASING INSTALLED: Threaded Welded
 10" Diam. from 1 1/2 ft. to 2 1/2 ft. Gage 25
 " Diam. from ft. to ft. Gage
 " Diam. from ft. to ft. Gage

Work started 3-21 1966 Completed 4-7 1966
 Date well drilling machine moved off of well 4-7 1966

(7) PERFORATIONS: Perforated? Yes No
 Type of perforator used Mills knife 10"
 Size of perforations 10" mills knife
 perforations from ft. to ft.
 2000 perforations from 25 ft. to 212 ft.

(8) SCREENS: Well screen installed? Yes No
 Manufacturer's Name
 Model No.
 Slot size Set from ft. to ft.
 Diam. Slot size Set from ft. to ft.

(13) PUMP: Manufacturer's Name
 Type: H.P.

(9) CONSTRUCTION: Well seal—Material used in seal Bentonite
 Depth of seal 18 ft. Was a packer used? no
 Diameter of well bore to bottom of seal 13 in.
 Were any loose strata cemented off? Yes No Depth
 Was a drive shoe used? Yes No
 Was well gravel packed? Yes No Size of gravel:
 Gravel placed from ft. to ft.
 Did any strata contain unusable water? Yes No
 Type of water? depth of strata
 Method of sealing strata off

Water Well Contractor's Certification:
 This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
CHRISTENSEN DRILLING & IRRIGATION
 NAME 3550 West 18th, Eugene, Oregon 97402 (Type or print)
 Address Eugene, Oregon 97402
 Drilling Machine Operator's License No. 406
 [Signed] Mark Christensen (Water Well Contractor)
 Contractor's License No. 97 Date 4-25, 1966

(10) WATER LEVELS:
 Static level 2 1/2 ft. below land surface Date 4/1/66
 Artesian pressure lbs. per square inch Date