NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON JUN 1 7 1975 State Well No. 175 /4W - 26 (Please type or print) STATE ENGINEER State Permit No. LANE

(Do not write above this line) LEM, OREGON 1919

(1) OWNER:	(10) LOCATION OF WELL:
Name Barker Willamette	County Lane Driller's well number C/18/T
Address 118 Pacific HiWay	14 14 Section 26 T. 17SR. 4W W.M.
Fugene, Oregon 97402	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(a) PROPERTY (check)	
(0) (1)	Depth at which water was first found 20 ft.
Rotary Driven Domestic Industrial Manuscipal Cable Definition	Static level 20 ft. below land surface. Date 5/19/75
Cable	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded Welded 250 10 "Diam. from 0 128 ft. Gage 250 "Diam. from ft. to ft. Gage Threaded	(12) WELL LOG: Diameter of well below casing 10 Depth drilled 130 ft. Depth of completed well 130 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
March Cort	MATERIAL From To SWL
Type of perforator used	Back fill 0 3
	Brown black clay 3 14
80 perforations from 20 ft, to 30 ft.	Brown clay & small gravel v 14 19
60 perforations from 122 ft. to 126 ft.	Medium gravel 19 25
perforations fromft. toft.	Brown clay & gravel 25 63
(7) SCREENS: Well screen installed? Yes In No	Grev clay & gravel 63 68
Manufacturer's Name	Brown clay & gravel 68 81
Type	Brown claw 81 88
Diam. Slot size Set from ft. to ft.	Blue clay 88 93
Diam. Slot size Set from ft. to ft.	Grey clay 93 114
	Grey sandy clay 114 123
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Black sand & gravel 123 126
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	(tray shale 126 130
gal./min. with ft. drawdown after hrs.	West of the second seco
1, gair, min. water 20 and 10	
The state of the s	
" " " " " " " " " " " " " " " " " " "	
Bailer test 200 gal./min. with 70 ft. drawdown after 31 hrs.	
Artesian flow g.p.m.	The land of the second
perature of water Depth artesian flow encountered ft.	Work started 5/16/75 19 Completed 5/23/75 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5/23/75 19
Comont	Drilling Machine Operator's Certification:
Well Seal-Indicated asset	This well was constructed under my direct supervision
Well sealed from land surface to	Materials used and information reported above are true to my best knowledge and belief.
10	[Signed] Machine Operator) Date 5/31/759
Number of sacks of cement used in well seal \$27 sacks	(Drifling Machine Operator)
Number of sacks of bentonite used in well sealsacks	Diffille Machine Operator b Excourse Fire
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.	Name Corvellis Drilling Co. Inc.
Did any strata contain unusable water? Yes No	(Person firm or corporation) (Type or print)
Type of water? depth of strata	Address 3440 SW 3rd St. Corvallis, Oregon 9733
	May Aking
Method of sealing strata off Was well gravel packed? ☐ Yes ☒ No Size of gravel:	(Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No
tiravel placed fromIL tolt.	