OBSERVATION WELL

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

6

STATE ENGINEER WATER WELL REPORT
CALE OF CRESCIENCE STATE OF OREGON

State Well No. State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level	s -
Name West Lawn Memorial Cemetery	Was a pump test made? 🛛 Yes 🔲 No If yes, by whom? Well	Driller
Address Rt. 5, Box 171	Yield: 60 gal./min. with 20 ft. drawdown after	1 hrs.
Eugene, Oregon	n n	***
(2) LOCATION OF WELL:))))))	******
County Lane Owner's number, if any—	Bailer test gal./min. with ft. drawdown after	hrs.
71. 76. 1/4 71. E 1/4 Section 33 T. 17S R. 4W W.M.	Artesian flow g.p.m. Date Temperature of water Was a chemical analysis made? Yes	1KI No
Bearing and distance from section or subdivision corner		***
North	(12) WELL LOG: Diameter of well	
17 Feet South of AProperty line	Deput diffied C C In Deput of Company	.50 ft.
73 Feet West of East Property line	Formation: Describe by color, character, size of material and struct show thickness of aquifers and the kind and nature of the material stratum penetrated, with at least one entry for each change of fo	ure, and i in each rmation.
	MATERIAL FROM	то
(3) TYPE OF WORK (check):	Dirt, clay 0	8
New Well ♣ Deepening ☐ Reconditioning ☐ Abandon ☐	Clay & gravel (fairly compact 8	25
If abandonment, describe material and procedure in Item 11.	Sand & gravel (varied from 25	_51_
THE PROPERTY OF THE LA	mostly sand with little water	
PROPOSED USE (check): (5) TYPE OF WELL:	to loose sand & gravel with fair	
Domestic Industrial Municipal Rotary Driven Cable	amounts of water) Clay 51	-54-
Irrigation Test Well Other Dug Bored		750
(6) CASING INSTALLED: Threaded □ Welded □	formation water bearing at 54	150
5/8 Olbiam from O at to 54 ft. Gage 188wal	1 the 115 ft. level and an increase beyond 0	
"Diam. fromft. Gage	Increase beyondy	
" Diam. from ft. to ft. Gage	Bottom of hole	
(T) DEDUCT ANIONS.		
(7) PERFORATIONS: Perforated? ✓ Yes ☐ No Type of perforator used Mills		
Type of perforation used M1118 SIZE of perforations in. by 2 in.		
130 perforations from 25 ft. to 51 ft.		
perforations fromft. toft.		
perforations from ft. to ft.		-
perforations from ft. to ft.		
perforations fromft. toft.		
(8) SCREENS: Well screen installed ☐ Yes ➤ No		
Manufacturer's Name		
Type Model No		
Diem. Slot size Set from ft. to ft.		
Slot size Set from ft, to ft.	Work started 8-14-59 19 . Completed 8-21-59	19
(9) CONSTRUCTION:	(13) PUMP:	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	Manufacturer's Name	
Gravel placed fromft, toft.	Type: H.P.	
Was a surface seal provided? Tes INo To what depth?ft.		
Material used in seal—	Well Driller's Statement:	
Did any strata contain unusable water? Yes No	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Type of water? Depth of strata	`	
Method of sealing strata off	NAME Wayne Hayes Well Drilling (Person, firm, or corporation) (Type or print)	
(10) WATER LEVELS:	Address 535 Coburg Road, Eugene, Oregon	
Static level 9 ft. below land surface Dat8-21-59	9	
Artesian pressure lbs. per square inch Date	Driller's well number	
Log Accepted by:	[Signed] Mayne (Well Driller)	
[Signad] C. A. Handel acknote Sopt 5 1059	(Well, Driller)	
(Owner)	License No	., 19