SALEM CH.

The original and first contractor of this report are to be filed with the STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion. (Do not write above this line)

State Well No. State .. 52

е	Permit	No.	
	: ₹		12787

, / 			
(1) OWNER:	(10) LOCATION OF WELL:		
Name EUGENE YACHT CLUB	County ANE Driller's well nu	mber	
Address 1375 11 MA AVE W	½ ½ Section 5 T. 17a	R. 5W	W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	on corner	
New Well Deepening Reconditioning Abandon A			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 65		ft.
Rotary Driven Domestic Maintenant Municipal Domestic Maintenant Domestic Maintenant Domestic	Static level 6 2 ft. below land s	urface. Date 🗲	-20-71
Dug	Artesian pressure lbs. per squar	e inch. Date	
CASING INSTALLED: Threaded Welded Wilded ft. to ft. Gage ft. Gage	(12) WELL LOG: Diameter of well b		, ?
"Diam. fromft. toft. Gage	Depth drilled /O ft. Depth of comple	eted well /O	Oft.
	Formation: Describe color, texture, grain size a		
PERFORATIONS: Perforated? MY Yes No.	and show thickness and nature of each stratur with at least one entry for each change of format position of Static Water Level and indicate prin	tion. Report each	change in
Type of perforator used	MATERIAL	From To	swL
Size of perforations $3/8$ in. by $3\frac{1}{2}$, in.	SANDY CLAY WIGRAVEL	0 50	1
48 perforations from 65 ft. to 70 ft.	1.35 (
perforations from ft. to ft.	SAND & GRAVEL WICLAY BADE	N50 65	
perforations from ft. to ft.		·	
(E) CODERING	COURSE BROWN SAMD WOLD	65 69	<u> </u>
(7) SCREENS: Well screen installed? Yes No	GRAVEL SOME CLAY		
Manufacturer's Name	diameter of	10 7A	
Type	CLAY W/5 46	69 78	+
Diam. Slot size Set from ft. to ft.	BROUN SAND FINE	78 87	
District Control of the Control of t	UNOUN SAME TONE	70 02	+
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	BLUE CLAY	82 100	
Was a pump test made? Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
			<u> </u>
" " " "			
Baller test 7 30 gal./min. with MAX ft. drawdown after / hrs.			-
Artesian flow g.p.m.	air air		
mperature of water Depth artesian flow encountered ft.	Work started 5 - 10 1971 Complete	ed 5-20	19 7/
(9) CONSTRUCTION:	Date well drilling machine moved off of well	5 - 20	197/
Well seal-Material used CEMENT & BENTONITE	Drilling Machine Operator's Certification:		
Well sealed from land surface to 65 ft.	This well was constructed under my		
Diameter of well bore to bottom of seal 978 571 in.	Materials used and information reported best knowledge and belief	above are iri	ie to my
Diameter of well bore below sealin.	[Signed] Mark Muslimus	Date 5- 20	197/
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	1	•
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.		
Brand name of bentonite 1/ELLOWSTONIS	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons of water 40 lbs./100 gals.	This well was drilled under my jurisdi		report is
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and bel	FAL	
Did any strata contain unusable water? ☐ Yes ☒ No	(Person, firm or corporation)	(Type or p	rint)
Type of water? depth of strata	Address 3550 W18-4 EC	CENE	
Method of sealing strata off	M. IN.	-	
Was well gravel packed? ☐ Yes Ŋ No Size of gravel:	[Signed] (Water Well Contr	actor)	
Gravel placed from ft. to ft.	Contractor's License No	-20	197/
	,		,